

LUBRICANT FOR MOUNTING TIRES

**SOCOLUB V0690 is a lubricant used to ease the mounting and dismounting of tires.
SOCOLUB V0690 was formerly sold under the trademark of BIB'UP (cf. Certificate of Analysis from MICHELIN)**

Does not develop corrosion on steel or aluminium alloys.

Dries quickly and eliminates any rotation risk of the tire on the rim.

SOCOLUB V0690 is supplied in aerosol:

- Rapidly ready to use, precise application and easy mounting.
 - Does not deteriorate under the action of external polluting agents.
 - Does not run, leaves the environment clean and safe for the user.
 - Optimized consumption as applies just the right quantity of product.
-
- Bacteriostatique: no bacterial development, no odor development.
 - One spray allows 100 mountings.

USES

- Product used for lubricating between the rim and the tire for mounting and dismounting car, van and motorbike tires.
- Can be used at ambient temperature (resistant to cold).

DIRECTIONS FOR USE

1- Dismounting:

After having positioned the tool head, spray the product between the tire and the rim. Dismount the tire.

2- Mounting:

Position the rim on the mounting plate and lubricate the rim and the tire bead. When re-mounting the tire positioned itself easily thanks to the optimum penetration of the lubricant.

Since the product dries quickly (10-15 minutes) you may carry out the wheel balancing operation just after mounting.

TECHNICAL CHARACTERISTICS

Appearance clear colourless liquid



Density 1.0

PRECAUTIONS FOR USE AND STORAGE

Store in original closed packages, far from heat in a temperate area. Do not expose to a temperature superior to 50°C (122°F).

Please read the safety data sheet for more information.

This technical data sheet replaces and cancels the previous one.

The above details have been compiled to the best of our knowledge, they have, however, an indicative value only, and we therefore make no warranties and assume no liability in connection with any use of this information, particularly if a third party's rights are affected by the use of our products. The above information has been compiled based upon tests carried out by Socomore ; all data is subject to change as Socomore deems appropriate. The data given is not intended to substitute for any testing you must conduct in order to determine the suitability of the product for your particular purposes. Please check your local legislation applicable to the use of this product. Should you need any further information please contact our services.



Support technique International / International Technical Support
tel. +33 (0)2 97 43 76 90 fax +33 (0)2 97 54 50 26 E-mail Support@socomore.com
Pour connaître notre correspondant le plus proche / To find our nearest correspondent
socomore@socomore.com

socomore
finishing solutions