

- ✓ Zero hazard classification - Toxicity and Ecotoxicity
- ✓ Improve working conditions > Soft odor
- ✓ Zero fire risk related to its use - non flammable product
- ✓ Zero transport constraints



## HIGH FLASH POINT CLEANING SOLVENT

High flash point solvent based cleaner, VOC free controlled volatility. It is used to remove paint, ink, marker, varnish, adhesive, resins, oil and grease from metal and composite parts.

### n-Butyl acetate

### DIESTONE ZERO HD

	n-Butyl acetate	DIESTONE ZERO HD
Hazard statements	H225 - Highly flammable liquid and vapor. H336 - May cause drowsiness or dizziness.	N/A
Flash point	22 ° C / 71.6 ° F	99°C / 212°F
VOC	100 % VOC	VOC Free
Evaporation rate (N - butyl acetate)	1	<0.03
Specific gravity value (kg/m3)	880	1100
Cleaner odor	Medium	Soft

# A "ONE FOR ONE" PRODUCT REPLACEMENT



## > CLEANING EFFICIENCY

Pollutants	n-Butyl acetate	DIESTONE ZERO HD
	on steel, aluminium, carbon fiber	on steel, aluminium, carbon fiber
Grease	✓	✓
Oil	✓	✓
Dust	✓	✓
Paint	✓	✓
Un-cured Resine / Sealant	✓	✓

## > APPROVED OPERATIONS

	n-Butyl acetate	DIESTONE ZERO HD
Degreasing	✓	✓
General degreasing	✓	✓
Paint equipment cleaning	✓	✓
Wet/Uncured sealant & adhesive removal	✓	✓

## ALSO AVAILABLE IN PRE-SATURATED FORM FOR FURTHER COST REDUCTIONS

### ELIMINATE BULK LIQUIDS



- Eliminate manual saturation process
- Standardize cleaning operations
- Reduce consumption



- Improve quality & production performance
- No VOC emissions
- Reduce waste & environmental impact
- Improve working conditions - no risk of slips, falls or fires
- Eliminate hazardous liquid transport, storage & logistics



### REDUCE OPERATIONAL COSTS

