# Technical Data Sheet - Fiche Technique

### Approvals and conformities

ASME RCC-M ISO 9934-2 NFF 00-090 ASTM-E-1444

PMUC (French acronym for : Products and Equipments allowed for use in Powerplants by EDF - French Electricity Bo

< 200ppm

## MANUFACTURER: Babb Co (FR)

## **DESCRIPTION / APPLICATION(S):**

Primarily to wipe off the white background B 104A used for magnetic testing. Can also be used as a degreasing agent prior to penetrant testing, although cleaner N 120 is better.

Companion products: White background B 104A

# **DIRECTIONS FOR USE**

To wipe off the B 104A white background after magnetic testing, spray B 105 and wipe with a rag, until the white layer disappears.

# TECHNICAL CHARACTERISTICS

- Non-chlorinated propelling agent	
- Highly volatile, low toxicity product, offering a pleasant fruity s	mell
Halogenous content	< 2

# PRECAUTIONS FOR USE AND STORAGE

Transport / Handling: Refer to Material Safety Data Sheet (MSDS).

Storage: Keep away from moisture

Temperature range: 0°C à 50° C (32°F to 122°F).

Keep packaging closed after taking out some of the product





# 1 Date: 04-07-2017 Written and checked by: F. Héron

### This technical data sheet replaces and cancels the previous one.

The above details have been compiled to the best of our knowledge. They have, however, an indicative value only and we therefore make no warranties and assume no liability in connection with any use of this information, particularly if a third party's rights are affected by the use of our products. The above information has been compiled based upon tests carried out by SOCOMORE. All data is subject to change as Socomore deems appropriate. The data given is not intended to substitute for any testing you must conduct in order to determine the suitability of the product for your particular purposes. Please check your local legislation applicable to the use of this product. Should you need any further information please contact us.



