

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

DIESTONE A 8290

Regulation (EU) n. 2020/878

Safety Data Sheet date: 8/2/2024, version 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: DIESTONE A 8290
SDS code: P28290
UFI: FP3D-MHKT-9M24-8KDS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Solvent
Cleaner
Industrial uses

Uses advised against:

No uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Manufacturers:

Socomore SASU
Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France
Tel : +33 (0)2 97 43 76 83 - Fax : +33 (0)2 97 54 50 26
Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax
+353 21 4889923 / ireland@socomore.com

Distributors:

Socomore SASU
Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France
Tel : +33 (0)2 97 43 76 83 - Fax : +33 (0)2 97 54 50 26
Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax
+353 21 4889923 / ireland@socomore.com

Competent person responsible for the safety data sheet:

techdirsocomore@socomore.com

1.4. Emergency telephone number

France : ORFILA (INRS) +33 (0)1 45 42 59 59
International : CHEMTEL +1-813-248-0585.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

- ⚠ Warning, Flam. Liq. 3, Flammable liquid and vapour.
- ⚠ Warning, STOT SE 3, May cause drowsiness or dizziness.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
DIESTONE A 8290



Warning

Hazard statements:

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing vapours.

P312 Call a POISON CENTER if you feel unwell.

P370+P378 In case of fire, use a CO2 fire extinguisher to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Contains

2-methoxy-1-methylethyl acetate

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.






3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number		Classification
$\geq 70\%$ - $< 80\%$	2-methoxy-1-methylethyl acetate	Index number: CAS: EC: REACH No.:	607-195-00-7 108-65-6 203-603-9 01-2119475791-29	<div> 2.6/3 Flam. Liq. 3 H226 3.8/3 STOT SE 3 H336 </div> EUH066
$\geq 15\%$ - $< 20\%$	(2-Methoxymethylethoxy)-propanol	Index number: CAS:	603_998_97_1 34590-94-8	Substance with a Union workplace exposure limit.

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

DIESTONE A 8290

		EC: 252-104-2 REACH No.: 01-2119450011-60	
>= 7% - < 10%	HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS	EC: 919-857-5 REACH No.: 01-2119463258-33	 2.6/3 Flam. Liq. 3 H226  3.10/1 Asp. Tox. 1 H304  3.8/3 STOT SE 3 H336 EUH066
>= 0.001% - < 0.1%	1-methoxy-2-propanol; monopropylene glycol methyl ether	Index number: 603-064-00-3 CAS: 107-98-2 EC: 203-539-1 REACH No.: 01-2119457435-35	 2.6/3 Flam. Liq. 3 H226  3.8/3 STOT SE 3 H336

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not induce vomiting. Obtain a medical examination.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Redness.

Repeated exposure may cause skin dryness or cracking.

Burning sensation.

Swelling

Blurred vision.

Temporary burning sensation in the nose and throat.

Cough

Difficult breathing.

Vapours may cause drowsiness and dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

DIESTONE A 8290

safety data sheet if possible).

Treatment:

Treat symptomatically.

Call a doctor or poison control center for further instructions.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, ensure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

7.2. Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Store at ambient temperatures. Keep away from unguarded flame and heat sources. Avoid direct

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

DIESTONE A 8290

exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

- OEL Type: ACGIH - TWA(8h): 150 ppm - STEL: 100 ppm

- OEL Type: National - TWA(8h): 275 mg/m³, 50 ppm - STEL: 550 mg/m³, 100 ppm -

Behaviour: Binding - Notes: France VLEPC

- OEL Type: National - TWA(8h): 270 mg/m³, 50 ppm - Notes: GERMANY

- OEL Type: National - TWA(8h): 274 mg/m³, 50 ppm - STEL: 548 mg/m³, 100 ppm -

Notes: UK (WELs)

- OEL Type: National - TWA: 260 mg/m³ - STEL: 520 mg/m³ - Notes: POLAND

- OEL Type: EU - TWA(8h): 275 mg/m³, 50 ppm - STEL: 550 mg/m³, 100 ppm - Notes:

Skin

- OEL Type: AIHA

- TWA: 50 ppm

- OEL Type: National - TWA: 275 mg/m³, 50 ppm - STEL(5 min (Mow)): 550 mg/m³, 100 ppm - Notes: Österreich

- OEL Type: National - TWA: 270 mg/m³, 50 ppm - Notes: Norway (Skin)

(2-Methoxymethylethoxy)-propanol - CAS: 34590-94-8

- OEL Type: National - TWA(8h): 310 mg/m³ - Notes: Germany - Notes DFG, EU

- OEL Type: National - TWA(8h): 308 mg/m³, 50 ppm - Notes: France VLEC - TMP N° 84

- OEL Type: EU - TWA(8h): 308 mg/m³, 50 ppm - Notes: Skin

- OEL Type: National - TWA: 270 mg/m³ - STEL: 550 mg/m³ - Notes: Czech Republic

- OEL Type: ACGIH - TWA(8h): 50 ppm - Notes: Liver & CNS eff

- OEL Type: National - TWA(8h): 308 mg/m³, 50 ppm - Notes: UK - Skin

- OEL Type: National - TWA: 307 mg/m³, 50 ppm - STEL(5 min (Mow)): 614 mg/m³, 100 ppm - Notes: Österreich

- OEL Type: National - TWA: 308 mg/m³, 50 ppm - Notes: TWA Poland

- OEL Type: National - TWA: 240 mg/m³ - STEL: 480 mg/m³ - Notes: Poland (NDS, NDSch)

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

- OEL Type: National - TWA: 1200 mg/m³, 197 ppm - Notes: ExxonMobil

- OEL Type: National - TWA: 300 mg/m³ - STEL: 900 mg/m³ - Notes: Poland (NDS, DNSch)

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

- OEL Type: National - TWA(8h): 188 mg/m³, 50 ppm - STEL: 375 mg/m³, 100 ppm -

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

DIESTONE A 8290

Notes: France VLEC - INRS TMP N°84

- OEL Type: National - TWA: 370 mg/m³, 100 ppm - Notes: Germany
- OEL Type: National - TWA: 180 mg/m³ - STEL: 360 mg/m³ - Notes: Poland
- OEL Type: EU - TWA(8h): 375 mg/m³, 100 ppm - STEL: 563 mg/m³, 150 ppm - Notes: Skin
- OEL Type: ACGIH - TWA(8h): 50 ppm - STEL: 100 ppm - Notes: A4 - Eye and URT irr
- OEL Type: National - TWA: 187 mg/m³, 50 ppm - STEL(15min (Miw)): 187 mg/m³, 50 ppm - Notes: Austria
- OEL Type: National - TWA(8h): 375 mg/m³, 100 ppm - STEL(15min (Miw)): 560 mg/m³, 150 ppm - Notes: United Kingdom - Skin
- OEL Type: National - TWA(8h): 188 mg/m³, 50 ppm - STEL: 375 mg/m³, 100 ppm - Notes: Canada (Gazette Officielle du Québec, January 4, 2023, Vol. 155, No.1)
- OEL Type: National - TWA: 180 mg/m³, 50 ppm - Notes: Norway (skin)

DNEL Exposure Limit Values

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Worker Industry: 796 mg/kg b.w./day - Consumer: 320 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 275 mg/m³ - Consumer: 33 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 36 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Industry: 550 mg/m³ - Consumer: 33 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects

(2-Methoxymethylethoxy)-propanol - CAS: 34590-94-8

Worker Industry: 65 mg/kg b.w./day - Consumer: 15 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 310 mg/m³ - Consumer: 37.2 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 1.67 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic effects

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Worker Industry: 208 mg/kg b.w./day - Consumer: 125 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 871 mg/m³ - Consumer: 185 mg/kg b.w./day - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 125 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic effects

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Worker Industry: 369 mg/m³ - Consumer: 43.9 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 50.6 mg/kg b.w./day - Consumer: 18.1 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 3.3 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Industry: 553.5 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

DIESTONE A 8290

(acute)

PNEC Exposure Limit Values

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Target: Fresh Water - Value: 0.635 mg/l

Target: Marine water - Value: 0.0635 mg/l

Target: Microorganisms in sewage treatments - Value: 100 mg/l

Target: Freshwater sediments - Value: 3.29 mg/kg dw

Target: Marine water sediments - Value: 0.329 mg/kg dw

Target: Soil - Value: 0.29 mg/kg

Target: PNEC intermittent - Value: 6.35 mg/l

(2-Methoxymethylethoxy)-propanol - CAS: 34590-94-8

Target: Fresh Water - Value: 19 mg/l

Target: Marine water - Value: 1.9 mg/l

Target: Microorganisms in sewage treatments - Value: 4168 mg/l

Target: Freshwater sediments - Value: 70.2 mg/kg - Notes:: mg/kg p.s.

Target: Marine water sediments - Value: 7.02 mg/kg - Notes:: mg/kg p.s.

Target: Soil (agricultural) - Value: 2.74 mg/kg - Notes:: mg/kg p.s.

Target: Water (intermittent discharge) - Value: 190 mg/l

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Target: Fresh Water - Value: 10 mg/l

Target: Freshwater sediments - Value: 41.6 mg/kg

Target: Marine water sediments - Value: 4.17 mg/kg

Target: Soil (agricultural) - Value: 2.47 mg/kg

Target: Microorganisms in sewage treatments - Value: 100 mg/l

Target: Marine water - Value: 1 mg/l

Target: Water (intermittent discharge) - Value: 100 mg/l

Biological Exposure Index

N.A.

8.2. Exposure controls

See below, example of PPE to use.

Eye protection:

Safety goggles (EN 166)

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Suitable gloves type: NF EN374

Butyl rubber (isobutylene-isoprene copolymer)

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

Other conditions affecting workers exposure:

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

DIESTONE A 8290

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Physical state:	Liquid	--	--
Colour:	Colourless	--	--
Odour:	N.A.	--	Solvent
Melting point/freezing point:	Not Relevant	--	--
Boiling point or initial boiling point and boiling range:	145 °C	NF T67-101	--
Flammability:	Flam. Liq. 3, H226	--	--
Lower and upper explosion limit:	0.6-7%	--	--
Flash point (°C):	41 °C	ISO 2592	--
Auto-ignition temperature:	260 °C	--	--
Decomposition temperature:	N.A.	--	--
pH:	Not Relevant	--	--
Kinematic viscosity:	<= 14 mm2/sec (40 °C)	--	--
Solubility in water:	5%	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient n-octanol/water (log value):	N.A.	--	--
Vapour pressure:	1,8 mmHg (20 °C)	--	--
Density and/or relative density:	0.94	ISO 649, ASTM D1298	--
Relative vapour density:	4.5	--	--
Particle characteristics:			

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

DIESTONE A 8290

Particle size:	N.A.	--	--
----------------	------	----	----

9.2. Other information

Properties	Value	Method:	Notes
Explosive properties:	yes	--	May form explosive mixtures with air.
Evaporation rate:	0.24	NFT 30-301	(n-butyl acetate=1)

Volatile Organic compounds - VOCs = 930 g/l

N.A. = not available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological information of the product:

DIESTONE A 8290

Acute toxicity

Not classified

Based on available data, the classification criteria are not met

Skin corrosion/irritation

Not classified

Based on available data, the classification criteria are not met

Serious eye damage/irritation

Not classified

Based on available data, the classification criteria are not met

Respiratory or skin sensitisation

Not classified

Based on available data, the classification criteria are not met

Germ cell mutagenicity

Not classified

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

DIESTONE A 8290

Based on available data, the classification criteria are not met

Carcinogenicity

Not classified

Based on available data, the classification criteria are not met

Reproductive toxicity

Not classified

Based on available data, the classification criteria are not met

STOT-single exposure

The product is classified: STOT SE 3 H336

STOT-repeated exposure

Not classified

Based on available data, the classification criteria are not met

Aspiration hazard

Not classified

Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg - Source: OECD 401

Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg - Source: OECD 402

Test: LC50 - Route: Inhalation - Species: Rat > 10.8 mg/l

Test: LC50 - Route: Skin - Species: Rabbit > 5000 mg/kg - Source: OECD 402

Test: LC0 - Route: Inhalation Vapour - Species: Rabbit = 23.5 mg/l - Source: OECD 403

Test: ATE - Route: Oral > 5000 mg/kg

Test: ATE - Route: Inhalation Vapour > 23.5 mg/l - Duration: 6 hours

Test: ATE - Route: Skin > 5000 mg/kg

(2-Methoxymethylethoxy)-propanol - CAS: 34590-94-8

Acute toxicity

ATE - Oral 5001 mg/kg bw

ATE - Dermal 9510 mg/kg bw

ATE - Inhalation (Vapours) 3,35 mg/l

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit = 9510 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 3350 mg/m3 - Notes: aerosol, 7h

Test: ATE - Route: Oral > 5000 mg/kg

Test: ATE - Route: Inhalation Vapour = 3.35 mg/l - Duration: 7h

Test: ATE - Route: Skin = 9510 mg/kg

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg - Duration: 4h - Source: OECD 401

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg - Duration: 24 hours - Source: OECD 402

Test: LC50 - Route: Inhalation - Species: Rat > 4951 mg/m3 - Duration: 4h - Source: OECD 403

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

DIESTONE A 8290

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 5 mg/l - Duration: 4h

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration $\geq 0.1\%$

Other toxicological information:

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Irritating to eyes and skin.

Repeated exposure may cause dryness or cracking of the skin.

Inhalation of vapours may cause drowsiness and dizziness.

Inhalation - May irritate respiratory tracts.

Inhalation of vapours may cause headaches, nausea, vomiting and impaired consciousness.

Ingestion:

Severe lung damage, irritation of the digestive tract, nausea, vomiting and diarrhea. Risk of central nervous system depression.

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

DIESTONE A 8290

Not classified for environmental hazards

Based on available data, the classification criteria are not met

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Aquatic plants > 1000 mg/l - Duration h: 72 - Notes: Selenastrum capricornutum, OECD 201

Endpoint: LC50 - Species: Fish = 134 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss, OECD 203

Endpoint: EC50 - Species: Invertebrates > 500 mg/l - Duration h: 48 - Notes: Daphnia magna

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish = 47.5 mg/l - Duration h: 336 - Notes: Oryzias latipes, OECD 204

Endpoint: NOEC - Species: Invertebrates > 100 mg/l - Duration h: 504 - Notes: Daphnia magna, OECD 202

(2-Methoxymethylethoxy)-propanol - CAS: 34590-94-8

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96 - Notes: Poecilia reticulata

Endpoint: LC50 - Species: Daphnia > 1000 mg/l - Duration h: 96 - Notes: Crangon crangon

Endpoint: EC50 - Species: Algae > 969 mg/l

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia > 0.5 mg/l - Duration h: 528 - Notes: LOEC: > 0,5 mg/l, 22 days

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

DIESTONE A 8290

e) Plant toxicity:

Endpoint: NOEC = 250000 mg/l

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss

Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 72 - Notes: Pseudokirchnerella subcapitata

Endpoint: EC50 - Species: Daphnia > 1000 mg/l - Duration h: 48 - Notes: Daphnia magna

Endpoint: DSEO-R (NOELR) - Species: Algae = 3 mg/l - Duration h: 72 - Notes:

Pseudokirchnerella subcapitata - biomass - OECD 201)

Endpoint: DSEO-R (NOELR) - Species: Algae = 100 mg/l - Duration h: 72 - Notes:

Pseudokirchnerella subcapitata - growth rate - OECD 201)

b) Aquatic chronic toxicity:

Endpoint: DSEO-R (NOELR) - Species: Daphnia = 0.23 mg/l - Duration h: 504 - Notes: Daphnia magna - QSAR Petrotox

Endpoint: DSEO-R (NOELR) - Species: Fish = 0.13 mg/l - Duration h: 672 - Notes: Oncorhynchus mykiss - QSAR Petrotox

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96 - Notes: Leuciscus idus, LC/EC/IC50

Endpoint: LC50 - Species: Daphnia > 1000 mg/l - Duration h: 48 - Notes: LC/EC/IC50

Endpoint: LC50 - Species: Algae > 1000 mg/l - Notes: LC/EC/IC50

Endpoint: LC50 - Species: Fish < 4600 mg/l - Duration h: 96 - Notes: Leuciscus idus

12.2. Persistence and degradability

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Biodegradability: Biological oxygen demand (BOD) - Test: OECD 301F - Duration: 28 days - %: 83% - Notes: ISO 9408; 92/69/CEE, C.4-D

(2-Methoxymethylethoxy)-propanol - CAS: 34590-94-8

Biodegradability: Biodegradability rate - Test: OECD 301F - Duration: 28 days - %: 75

Biodegradability: Biodegradability rate - Test: OECD 302B - Duration: 13 days - %: 93

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Biodegradability: Biodegradability rate - Duration: 28 days - %: 80%

Biodegradability: Photodegradation (in air)

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Biodegradability: Readily biodegradable

12.3. Bioaccumulative potential

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

BCF < 100

Log Pow < 3

(2-Methoxymethylethoxy)-propanol - CAS: 34590-94-8

Log Pow 1.01

BCF < 100

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Log Pow 0.37

12.4. Mobility in soil

N.A.

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

DIESTONE A 8290

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration $\geq 0.1\%$

12.7. Other adverse effects

No harmful effects expected.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Codes of wastes (Décision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste):

14 06 03* Other solvents and solvent mixtures

SECTION 14: Transport information



14.1. UN number or ID number

ADR-UN Number: 1993

IATA-UN Number: 1993

IMDG-UN Number: 1993

14.2. UN proper shipping name

ADR-Shipping Name: FLAMMABLE LIQUID, N.O.S. (2-methoxy-1-methylethyl acetate, HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS)

IATA-Shipping Name: FLAMMABLE LIQUID, N.O.S. (2-methoxy-1-methylethyl acetate, HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS)

IMDG-Shipping Name: FLAMMABLE LIQUID, N.O.S. (2-methoxy-1-methylethyl acetate, HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS)

14.3. Transport hazard class(es)

ADR-Class: 3

ADR - Hazard identification number: 30

IATA-Class: 3

IATA-Label: 3

IMDG-Class: 3

14.4. Packing group

ADR-Packing Group: III

IATA-Packing group: III

IMDG-Packing group: III

14.5. Environmental hazards

ADR-Environmental Pollutant: No

IMDG-Marine pollutant: No

IMDG-EmS: F-E , S-E

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

DIESTONE A 8290

14.6. Special precautions for user

ADR-Subsidiary hazards:	-
ADR-S.P.:	274 601
ADR-Transport category (Tunnel restriction code):	3 (D/E)
IATA-Passenger Aircraft:	355
IATA-Subsidiary hazards:	-
IATA-Cargo Aircraft:	366
IATA-S.P.:	A3
IATA-ERG:	3L
IMDG-Subsidiary hazards:	-
IMDG-Stowage and handling:	Category A
IMDG-Segregation:	-
Q.L.: 5L	
Q.E.: E1	

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)
Regulation (EU) n. 605/2014 (ATP 6 CLP)
Regulation (EU) n. 2015/1221 (ATP 7 CLP)
Regulation (EU) n. 2016/918 (ATP 8 CLP)
Regulation (EU) n. 2016/1179 (ATP 9 CLP)
Regulation (EU) n. 2017/776 (ATP 10 CLP)
Regulation (EU) n. 2018/669 (ATP 11 CLP)
Regulation (EU) n. 2018/1480 (ATP 13 CLP)
Regulation (EU) n. 2019/521 (ATP 12 CLP)
Regulation (EU) n. 2020/217 (ATP 14 CLP)
Regulation (EU) n. 2020/1182 (ATP 15 CLP)
Regulation (EU) n. 2021/643 (ATP 16 CLP)
Regulation (EU) n. 2021/849 (ATP 17 CLP)
Regulation (EU) n. 2022/692 (ATP 18 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

DIESTONE A 8290

Restriction 3

Restriction 40

Restrictions related to the substances contained:

Restriction 30

Restriction 75

Listed or in compliance with the following international inventories:

TSCA - Toxic Substances Control Act

The following substance(s) in this product has/have an identification by CAS number either in countries not affected by the REACH regulation or in regulations not yet updated to reflect the new naming convention for hydrocarbon solvents:

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)

Labelling of detergents (EC Regulations 648/2004 and 907/2006):

DIESTONE A 8290

aliphatic hydrocarbons $\geq 5\%$ - $< 15\%$

Labelling of biocides (Regulations 1896/2000, 1687/2002, 2032/2003, 1048/2005, 1849/2006, 1451/2007 and Directive 98/8/EC):

N.A.

N.A.

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

1999/13/EC (VOC directive)

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: P5c

15.2. Chemical safety assessment

No

1

Exposure scenarios exist for this product. You can request it at the following email address: techdirsocomore@socomore.com

SECTION 16: Other information

N.A.: Not Applicable or Not Available

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

DIESTONE A 8290

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

H304 May be fatal if swallowed and enters airways.

Hazard class and hazard category	Code	Description
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3

This safety data sheet has been completely updated in compliance to Regulation 2020/878.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 3, H226	On basis of test data
STOT SE 3, H336	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

CCNL - Appendix 1

Insert further consulted bibliography

Important confidentiality : this document contains confidential information that is proprietary to SOCOMORE. Subject to legal provisions determining otherwise, the distribution, republication or re-transmission of this document, in full or in part, must be limited to clearly identified individuals, either because they use the product, or to provide HSE information. Any communication of this document outside of this framework without our written consent is strictly forbidden.

SOCOMORE strongly advises every recipient of this safety data sheet to read it carefully and to consult experts in the field if necessary or appropriate, in order to understand the information it contains, notably the possible dangers associated with this product. The users must ensure the conformity and

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

DIESTONE A 8290

completeness of this information with regards to their specific use of the product.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the responsibility of the purchaser/user to ensure that their activities conform with current legislation in force.

The information is considered correct, but it is not exhaustive and it shall be used only as a guide which is based on the current knowledge of the substance or mixture and it is applicable to the safety precautions appropriate for the product.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
STOT SE:	May cause drowsiness or dizziness
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.