

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

Diestone SR

Safety Data Sheet dated 15/11/2021, version 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: Diestone SR
SDS code: P28294

UFI: G36R-5HGQ-EM2P-739U

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Cleaner

Industrial uses

Uses advised against:

No uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Manufacturers:

Socomore SASU

Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France

Tel : +33 (0)2 97 43 76 83 - Fax : +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax +353 21 4889923 / ireland@socomore.com

Distributors:

Socomore SASU

Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France

Tel : +33 (0)2 97 43 76 83 - Fax : +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax +353 21 4889923 / ireland@socomore.com

Socomore GmbH - c/o MAZARS GmbH - Theodor-Stern-Kai 1 - 60596 Frankfurt am Main - Deutschland - Tel: +33 (0)2 97 63 05 01

Socomore Iberia - Calle Diputació, 260 - 08007 Barcelona - Espana - Tel: +33 (0)2 97 63 05 01

SOCOMORE SPzoo - Ul. Piekna 18, 00-549 Warszawa Polska - Tel : +33 (0)2 97 63 05 01

Competent person responsible for the safety data sheet:

techdirsocomore@socomore.com

1.4. Emergency telephone number

France : ORFILA (INRS) +33 (0)1 45 42 59 59

International : CHEMTEL +1-813-248-0585.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

- ⚠ Warning, Flam. Liq. 3, Flammable liquid and vapour.
- ⚠ Danger, Eye Dam. 1, Causes serious eye damage.
- ⚠ Warning, STOT SE 3, May cause respiratory irritation.
- ⚠ Warning, STOT SE 3, May cause drowsiness or dizziness.
- ⚠ Danger, Asp. Tox. 1, May be fatal if swallowed and enters airways.

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

Diestone SR

⚠ Aquatic Chronic 2, Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H226 Flammable liquid and vapour.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P273 Avoid release to the environment.

P280 Wear protective gloves/clothing and eye/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER if you feel unwell.

P331 Do NOT induce vomiting.

P370+P378 In case of fire, use a CO2 fire extinguisher to extinguish.

P391 Collect spillage.

P403+P235 Store in a well-ventilated place. Keep cool.

Special Provisions:

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains

HYDROCARBONS, C10, AROMATICS, <1% NAPHTHALENE

ethyl (S)-2-hydroxypropionate; ethyl L-lactate; ethyl-(S)-lactate

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))












Diestone SR

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
>= 70% - < 80%	HYDROCARBONS, C10, AROMATICS,<1% NAPHTHALENE	EC: 918-811-1 REACH No.: 01- 2119463583 -34	 3.10/1 Asp. Tox. 1 H304  3.8/3 STOT SE 3 H336  4.1/C2 Aquatic Chronic 2 H411 EUH066
>= 20% - < 25%	ethyl (S)-2- hydroxypropionate; ethyl L-lactate; ethyl-(S)- -lactate	Index number: 607-129-00-7 CAS: 687-47-8 EC: 211-694-1 REACH No.: 01- 2119516234 -49	 2.6/3 Flam. Liq. 3 H226  3.8/3 STOT SE 3 H335  3.3/1 Eye Dam. 1 H318
>= 0.3% - < 0.5%	naphthalene	Index number: 601-052-00-2 CAS: 91-20-3 EC: 202-049-5	 2.7/2 Flam. Sol. 2 H228  3.6/2 Carc. 2 H351  4.1/A1 Aquatic Acute 1 H400  4.1/C1 Aquatic Chronic 1 H410  3.1/4/Oral Acute Tox. 4 H302

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

Diestone SR

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

No particular treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

In case of fire, use a CO₂ fire extinguisher to extinguish.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

Diestone SR

Do not eat or drink while working.

7.2. Conditions for safe storage, including any incompatibilities

Avoid vapor emissions.

Always keep in a well ventilated place.

Store at ambient temperatures. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

HYDROCARBONS, C10, AROMATICS, <1% NAPHTHALENE

- OEL Type: National - TWA: 100 mg/m³, 17 ppm - Notes: ExxonMobil

- OEL Type: MAK - TWA: 50 mg/m³, 10 ppm - Notes: Ireland

ethyl (S)-2-hydroxypropionate; ethyl L-lactate; ethyl-(S)-lactate - CAS: 687-47-8

- OEL Type: National - TWA(8h): 25 mg/m³ - STEL: 49 mg/m³ - Notes: Finland

naphthalene - CAS: 91-20-3

- OEL Type: National - TWA(8h): 50 mg/m³, 10 ppm - Notes: INRS, France

- OEL Type: EU - TWA(8h): 50 mg/m³, 10 ppm

- OEL Type: ACGIH - TWA(8h): 10 ppm - Notes: Skin, A3 - URT irr, cataracts, hemolytic anemia

- OEL Type: National - TWA: 50 mg/m³, 10 ppm - Notes: Ireland OELs

DNEL Exposure Limit Values

HYDROCARBONS, C10, AROMATICS, <1% NAPHTHALENE

Worker Industry: 12.5 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 150 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 7.5 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 32 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 7.5 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

ethyl (S)-2-hydroxypropionate; ethyl L-lactate; ethyl-(S)-lactate - CAS: 687-47-8

Target: Microorganisms in sewage treatments - Value: 0.4 mg/l

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

Diestone SR

Biological Exposure Index
N.A.

8.2. Exposure controls

See below, example of PPE to use.

Eye protection:

Safety goggles (EN 166)

Face protection shield. (EN 166)

Use closed fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Chemical protection clothing. (type 3 - EN14605)

Chemical protection clothing. (type 6 - EN13034)

Protection for hands:

Suitable gloves type: NF EN374

PVA (Polyvinyl alcohol).

Respiratory protection:

Use adequate protective respiratory equipment.

Mask with filter "A1" , brown colour (NF EN14387)

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

Other conditions affecting workers exposure:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Appearance and colour:	FLUID LIQUID	--	--
Odour:	N.A.	--	--
Odour threshold:	N.A.	--	--
pH:	N.A.	--	--
Melting point / freezing point:	Not Relevant	--	--
Initial boiling point and boiling range:	N.A.	--	--
Flash point (°C):	> 55 °C - <= 60 °C	EN ISO 2719	--
Flash Point (°F):	> 131 °F - <=	--	--

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

Diestone SR

	140 °C		
Evaporation rate:	N.A.	--	--
Solid/gas flammability:	N.A.	--	liquid
Upper/lower flammability or explosive limits:	0.6-11.4%	--	--
Vapour pressure:	< 1 kPa (20°C)	--	--
Vapour density:	> 1	--	--
Relative density:	< 1	--	--
Solubility in water:	N.A.	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient (n-octanol/water):	N.A.	--	--
Auto-ignition temperature:	337 °C	--	--
Decomposition temperature:	N.A.	--	--
Viscosity:	< 7 mm ² /s (40°C)	--	--
Explosive properties:	yes	--	May form explosive mixtures with air. (ethyl l-lactate)
Oxidizing properties:	N.A.	--	--

9.2. Other information

Properties	Value	Method:	Notes
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

Diestone SR

Substance Groups relevant properties	N.A.	--	--
--------------------------------------	------	----	----

Volatile Organic compounds - VOCs = 100 %

Volatile Organic compounds - VOCs = 910 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the product:

N.A.

Toxicological information of the main substances found in the product:

HYDROCARBONS, C10, AROMATICS, <1% NAPHTHALENE

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 4688 mg/m³

ethyl (S)-2-hydroxypropionate; ethyl L-lactate; ethyl-(S)-lactate - CAS: 687-47-8

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 5.6 mg/l - Duration: 4h

naphthalene - CAS: 91-20-3

Acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 0.4 mg/l - Duration: 4h

Test: LD50 - Route: Oral - Species: Mouse = 533 mg/kg

If not specified in other sections, the information required in Regulation (EU)2015/830 listed below must be considered as not relevant.:

Acute toxicity;

Skin corrosion/irritation;

Serious eye damage/irritation;

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

Diestone SR

Respiratory or skin sensitisation;
Germ cell mutagenicity;
Carcinogenicity;
Reproductive toxicity;
STOT-single exposure;
STOT-repeated exposure;
Aspiration hazard.

Other toxicological information:

ethyl (S)-2-hydroxypropionate; ethyl L-lactate; ethyl-(S)-lactate
Eye contact:
Severe eye damage
Specific target organ systemic toxicity - single exposure:
Irritating to respiratory tracts

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

HYDROCARBONS, C10, AROMATICS, <1% NAPHTHALENE

a) Aquatic acute toxicity:

Endpoint: EL50

- Species: Crustacea \geq 3 mg/l - Duration h: 48 - Notes: Daphnia magna

Endpoint: EL50

- Species: Crustacea \leq 10 mg/kg/d - Duration h: 48 - Notes: Daphnia magna

Endpoint: LL50

- Species: Fish \geq 2 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss

Endpoint: LL50

- Species: Fish $<$ 5 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss

Endpoint: NOELR - Species: Algae = 2.5 mg/l - Duration h: 72 - Notes: Pseudokirchnerella subcapitata

Endpoint: EL50

- Species: Algae = 11 mg/l - Duration h: 72 - Notes: Pseudokirchnerella subcapitata

ethyl (S)-2-hydroxypropionate; ethyl L-lactate; ethyl-(S)-lactate - CAS: 687-47-8

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Pseudokirchneriella subcapitata (green algae) $>$ 10 mg/l - Duration h: 70

Endpoint: LC50 - Species: Fish = 32 mg/l - Duration h: 96 - Notes: Pimephales promelas

b) Aquatic chronic toxicity:

Endpoint: EC50 - Species: Aquatic invertebrates = 83 mg/l - Duration h: 48 - Notes: Daphnia magna

12.2. Persistence and degradability

HYDROCARBONS, C10, AROMATICS, <1% NAPHTHALENE

Biodegradability: Biodegradability rate - Duration: 28 days - %: 50
naphthalene - CAS: 91-20-3

Biodegradability: Biodegradability rate - Duration: 28 days - %: 50

12.3. Bioaccumulative potential

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

Diestone SR

ethyl (S)-2-hydroxypropionate; ethyl L-lactate; ethyl-(S)-lactate - CAS: 687-47-8

Log Pow 0.06

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

No harmful effects expected.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Codes of wastes (Décision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste):

14 06 03* Other solvents and solvent mixtures

SECTION 14: Transport information



14.1. UN number

ADR-UN Number: 1993

IATA-UN Number: 1993

IMDG-UN Number: 1993

14.2. UN proper shipping name

ADR-Shipping Name: FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C10, AROMATICS,<1% NAPHTHALENE, ethyl

(S)-2-hydroxypropionate; ethyl L-lactate; ethyl-(S)-lactate)

IATA-Shipping Name: FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C10, AROMATICS,<1% NAPHTHALENE, ethyl

(S)-2-hydroxypropionate; ethyl L-lactate; ethyl-(S)-lactate)

IMDG-Shipping Name: FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C10, AROMATICS,<1% NAPHTHALENE, ethyl

(S)-2-hydroxypropionate; ethyl L-lactate; ethyl-(S)-lactate)

14.3. Transport hazard class(es)

ADR-Class: 3

ADR - Hazard identification number: 30

IATA-Class: 3

IATA-Label: 3

IMDG-Class: 3

14.4. Packing group

ADR-Packing Group: III

IATA-Packing group: III

IMDG-Packing group: III

14.5. Environmental hazards

ADR-Environmental Pollutant: Yes

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

Diestone SR

IMDG-Marine pollutant: Yes
Most important toxic component: HYDROCARBONS, C10, AROMATICS, <1%
NAPHTHALENE

14.6. Special precautions for user

ADR-Subsidiary hazards: -
ADR-S.P.: 274 601
ADR-Transport category (Tunnel restriction code): 3 (D/E)
IATA-Passenger Aircraft: 355
IATA-Subsidiary hazards: -
IATA-Cargo Aircraft: 366
IATA-S.P.: A3
IATA-ERG: 3L
IMDG-EmS: F-E , S-E
IMDG-Subsidiary hazards: -
IMDG-Stowage and handling: Category A
IMDG-Segregation: -
Q.L.: 5L
Q.E.: E1

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) 2015/830
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)
Regulation (EU) n. 605/2014 (ATP 6 CLP)
Regulation (EU) n. 2015/1221 (ATP 7 CLP)
Regulation (EU) n. 2016/918 (ATP 8 CLP)
Regulation (EU) n. 2016/1179 (ATP 9 CLP)
Regulation (EU) n. 2017/776 (ATP 10 CLP)
Regulation (EU) n. 2018/669 (ATP 11 CLP)
Regulation (EU) n. 2018/1480 (ATP 13 CLP)
Regulation (EU) n. 2019/521 (ATP 12 CLP)
Regulation (EU) n. 2020/217 (ATP 14 CLP)
Regulation (EU) n. 2020/1182 (ATP 15 CLP)
Regulation (EU) n. 2021/643 (ATP 16 CLP)

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

Diestone SR

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restriction 40

Restrictions related to the substances contained:

Restriction 75

Listed or in compliance with the following international inventories:

N.A.

The following substance(s) in this product has/have an identification by CAS number either in countries not affected by the REACH regulation or in regulations not yet updated to reflect the new naming convention for hydrocarbon solvents:

HYDROCARBONS, C10, AROMATICS, <1% NAPHTALENE (CAS: 64742-94-5)

Labelling of detergents (EC Regulations 648/2004 and 907/2006):

Diestone SR

aromatic hydrocarbons \geq 30%

Labelling of biocides (Regulations 1896/2000, 1687/2002, 2032/2003, 1048/2005, 1849/2006, 1451/2007 and Directive 98/8/EC):

N.A.

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

1999/13/EC (VOC directive)

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: P5c, E2

15.2. Chemical safety assessment

No

SECTION 16: Other information

N.A.: Not Applicable or Not Available

Full text of phrases referred to in Section 3:

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

Diestone SR

H411 Toxic to aquatic life with long lasting effects.
 EUH066 Repeated exposure may cause skin dryness or cracking.
 H226 Flammable liquid and vapour.
 H335 May cause respiratory irritation.
 H318 Causes serious eye damage.
 H228 Flammable solid.
 H351 Suspected of causing cancer.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H302 Harmful if swallowed.

Hazard class and hazard category	Code	Description
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Flam. Sol. 2	2.7/2	Flammable solid, Category 2
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Carc. 2	3.6/2	Carcinogenicity, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1
Aquatic Chronic 1	4.1/C1	Chronic (long term) aquatic hazard, category 1
Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 3, H226	On basis of test data
Eye Dam. 1, H318	Calculation method
STOT SE 3, H335	Calculation method
STOT SE 3, H336	Calculation method

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

Diestone SR

Asp. Tox. 1, H304	Calculation method
Aquatic Chronic 2, H411	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van
Nostrand Reinold

CCNL - Appendix 1

Insert further consulted bibliography

Important confidentiality : this document contains confidential information that is proprietary to SOCOMORE. Subject to legal provisions determining otherwise, the distribution, republication or re-transmission of this document, in full or in part, must be limited to clearly identified individuals, either because they use the product, or to provide HSE information. Any communication of this document outside of this framework without our written consent is strictly forbidden.

SOCOMORE strongly advises every recipient of this safety data sheet to read it carefully and to consult experts in the field if necessary or appropriate, in order to understand the information it contains, notably the possible dangers associated with this product. The users must ensure the conformity and completeness of this information with regards to their specific use of the product.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the responsibility of the purchaser/user to ensure that their activities conform with current legislation in force.

The information is considered correct, but it is not exhaustive and it shall be used only as a guide which is based on the current knowledge of the substance or mixture and it is applicable to the safety precautions appropriate for the product.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

Diestone SR

ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
STOT SE:	May cause drowsiness or dizziness
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.