

Safety Data Sheet

Diestone SR

Safety Data Sheet date: 1/15/2024, version 1

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: Diestone SR

Other means of identification:

SDS code: P28294

Recommended use of the chemical and restrictions on use

Recommended use:

Cleaner

Industrial uses

Restrictions on use:

No uses advised against are identified.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Manufacturers:

Socomore SASU

Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France

Tel : +33 (0)2 97 43 76 83 - Fax : +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax +353 21 4889923 / ireland@socomore.com

Distributors:

Dysol Inc. - 791 Westport Parkway - Fort Worth, TX 76177 / Phone: 1-817-335-1826 /
csr-na@socomore.com/ Fax Number: 817-335-2405

Socomore Canada Limited - Unit 204, 6741 Cariboo Road, Burnaby V3N 4A3, British Columbia, Canada / Email: csr-ca@socomore.com / Phone: +1 604 420 7707 / Fax: +1 604 420 7701

Competent person responsible for the safety data sheet:








techdirsocomore@socomore.com

Emergency phone number:

CHEMTEL: +1-813-248-0585 (International); 1-800-255-3924 (USA)

2. HAZARD(S) IDENTIFICATION

Classification of the chemical

-  Warning, Flam. Liq. 3, Flammable liquid and vapour.
-  Danger, Eye Dam. 1, Causes serious eye damage.
-  Warning, Carc. 2, Suspected of causing cancer.
-  Warning, STOT SE 3, May cause respiratory irritation.
-  Warning, STOT SE 3, May cause drowsiness or dizziness.
-  Danger, Asp. Tox. 1, May be fatal if swallowed and enters airways.
-  Aquatic Chronic 2, Toxic to aquatic life with long lasting effects.

Label elements

Hazard pictograms:

Safety Data Sheet

Diestone SR



Danger

Hazard statements:

- H226 Flammable liquid and vapour.
- H318 Causes serious eye damage.
- H351 Suspected of causing cancer.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H304 May be fatal if swallowed and enters airways.
- H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing vapours.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves and eye/face protection.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/...
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P312 Call a POISON CENTER/doctor/... if you feel unwell.
- P331 Do NOT induce vomiting.
- P370+P378 In case of fire, use a CO2 fire extinguisher to extinguish.
- P391 Collect spillage.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Safety Data Sheet

Diestone SR

Ingredient(s) with unknown acute toxicity:

None.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

>= 70% - < 80% HYDROCARBONS, C10, AROMATICS, <1% NAPHTHALENE

REACH No.: 01-2119463583-34, EC: 918-811-1

⚠ A.10/1 Asp. Tox. 1 H304

⚠ A.8/3 STOT SE 3 H336

⚠ US-HAE/C2 Aquatic Chronic 2 H411

>= 20% - < 25% ethyl (S)-2-hydroxypropionate; ethyl L-lactate; ethyl-(S)-lactate

REACH No.: 01-2119516234-49, Index number: 607-129-00-7, CAS: 687-47-8, EC: 211-694-1

⚠ B.6/3 Flam. Liq. 3 H226

⚠ A.8/3 STOT SE 3 H335

⚠ A.3/1 Eye Dam. 1 H318

>= 0.3% - < 0.5% naphthalene

Index number: 601-052-00-2, CAS: 91-20-3, EC: 202-049-5

⚠ A.6/2 Carc. 2 H351

⚠ US-HAE/A1 Aquatic Acute 1 H400

⚠ US-HAE/C1 Aquatic Chronic 1 H410

⚠ A.1/4/Oral Acute Tox. 4 H302

4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Remove contaminated clothing immediately and dispose of safely.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show the packing or label.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed

Safety Data Sheet

Diestone SR

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

No particular treatment.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

In case of fire, use a CO2 fire extinguisher to extinguish.

Unsuitable extinguishing media

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties: yes

Oxidizing properties: N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

Methods and materials for containment and cleaning up

Wash with plenty of water.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, ensure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

Conditions for safe storage, including any incompatibilities

Safety Data Sheet

Diestone SR

Avoid vapor emissions.
 Always keep in a well ventilated place.
 Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
 Avoid accumulating electrostatic charge.
 Keep away from food, drink and feed.
 Incompatible materials:
 None in particular.
 Instructions as regards storage premises:
 Cool and adequately ventilated.
 Safety electric system.
 Storage temperature:
 Store at ambient temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

HYDROCARBONS, C10, AROMATICS, <1% NAPHTHALENE

- OEL Type: National - TWA: 100 mg/m³, 17 ppm - Notes: ExxonMobil

ethyl (S)-2-hydroxypropionate; ethyl L-lactate; ethyl-(S)-lactate - CAS: 687-47-8

- OEL Type: National - TWA(8h): 25 mg/m³ - STEL(15min (Miw)): 49 mg/m³ - Notes:
 Finland

naphthalene - CAS: 91-20-3

- OEL Type: National - TWA(8h): 50 mg/m³, 10 ppm - Notes: INRS, France

- OEL Type: EU - TWA(8h): 50 mg/m³, 10 ppm

- OEL Type: ACGIH - TWA(8h): 10 ppm - Notes: Skin, A3 - URT irr, cataracts, hemolytic anemia

- OEL Type: National - TWA: 50 mg/m³, 10 ppm - Notes: Ireland OELs

DNEL Exposure Limit Values

HYDROCARBONS, C10, AROMATICS, <1% NAPHTHALENE

Worker Industry: 12.5 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 150 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 7.5 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 32 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 7.5 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

ethyl (S)-2-hydroxypropionate; ethyl L-lactate; ethyl-(S)-lactate - CAS: 687-47-8

Target: Microorganisms in sewage treatments - Value: 0.4 mg/l

Target: Fresh Water - Value: 0.32 mg/l

Target: Marine water - Value: 0.032 mg/l

Target: Freshwater sediments - Value: 1.66 mg/kg dw

Target: Marine water sediments - Value: 0.166 mg/kg dw

Safety Data Sheet

Diestone SR

Target: Soil - Value: 0.145 mg/kg dw

Appropriate engineering controls:

None

Individual protection measures

Eye protection:

Safety goggles (EN 166)

Face protection shield. (EN 166)

Use closed fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Chemical protection clothing. (type 3 - EN14605)

Chemical protection clothing. (type 6 - EN13034)

Protection for hands:

Suitable gloves type: NF EN374

PVA (Polyvinyl alcohol).

Respiratory protection:

Use adequate protective respiratory equipment.

Mask with filter "A1" , brown colour (NF EN14387)

Thermal Hazards:

None

9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Value	Method:	Notes
Physical state:	Liquid	--	--
Colour:	Clear	--	--
Odour:	N.A.	--	--
Odour threshold:	N.A.	--	--
pH:	N.A.	--	--
Melting point / freezing point:	Not Relevant	--	--
Initial boiling point and boiling range:	N.A.	--	--
Flash Point (°F):	> 131 °F - <= 140 °F	--	--
Flash point (°C):	> 55 °C - <= 60 °C	EN ISO 2719	--

Safety Data Sheet

Diestone SR

Evaporation rate:	N.A.	--	--
Solid/gas flammability:	N.A.	--	liquid
Upper/lower flammability or explosive limits:	0.6-11.4%	--	--
Vapour pressure:	< 1 kPa (20°C)	--	--
Vapour density:	> 1	--	--
Relative density:	< 1	--	--
Solubility in water:	N.A.	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient (n-octanol/water):	N.A.	--	--
Auto-ignition temperature:	337 °C	--	--
Decomposition temperature:	N.A.	--	--
Viscosity:	< 7 mm ² /s (40°C)	--	--
Explosive properties:	yes	--	May form explosive mixtures with air. (ethyl l-lactate)
Oxidizing properties:	N.A.	--	--

9.2. Other information

Properties	Value	Method:	Notes
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups	N.A.	--	--

Safety Data Sheet

Diestone SR

relevant properties			
---------------------	--	--	--

10. STABILITY AND REACTIVITY

Reactivity

It may generate dangerous reactions (See subsections below)

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

None

Conditions to avoid

Avoid accumulating electrostatic charge.

Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological information of the product:

Diestone SR

Acute toxicity

Not classified

Based on available data, the classification criteria are not met

Skin corrosion/irritation

Not classified

Based on available data, the classification criteria are not met

Serious eye damage/irritation

The product is classified: Eye Dam. 1 H318

Respiratory or skin sensitisation

Not classified

Based on available data, the classification criteria are not met

Germ cell mutagenicity

Not classified

Based on available data, the classification criteria are not met

Carcinogenicity

The product is classified: Carc. 2 H351

Reproductive toxicity

Not classified

Based on available data, the classification criteria are not met

STOT-single exposure

The product is classified: STOT SE 3 H335; STOT SE 3 H336

STOT-repeated exposure

Not classified

Based on available data, the classification criteria are not met

Aspiration hazard

The product is classified: Asp. Tox. 1 H304

Safety Data Sheet

Diestone SR

Toxicological information of the main substances found in the product:

HYDROCARBONS, C10, AROMATICS, <1% NAPHTHALENE

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg - Source: OECD 401

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg - Source: OECD 402

Test: LC50 - Route: Inhalation - Species: Rat > 2 mg/l

Test: LC50 - Route: Inhalation Vapour - Species: Rat > 4688 mg/m³ - Duration: 4h - Source: OECD 403

ethyl (S)-2-hydroxypropionate; ethyl L-lactate; ethyl-(S)-lactate - CAS: 687-47-8

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg - Source: OECD 401

Test: LC50 - Route: Inhalation - Species: Rat > 5400 mg/l - Duration: 4h - Source: OECD 403 - Notes: Atmosphère de test: poussières/brouillard / Test atmosphere: dust/mist

Test: NOAEL - Species: Rat = 3619 mg/kg bw

naphthalene - CAS: 91-20-3

Acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 0.4 mg/l - Duration: 4h

Test: LD50 - Route: Oral - Species: Mouse = 533 mg/kg

Substance(s) listed on the NTP report on Carcinogens:

naphthalene.

Substance(s) listed on the IARC Monographs:

naphthalene - Group 2B.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

None.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

Diestone SR

The product is classified: Aquatic Chronic 2 - H411

HYDROCARBONS, C10, AROMATICS, <1% NAPHTHALENE

a) Aquatic acute toxicity:

Endpoint: EL50

- Species: Crustacea >= 3 mg/l - Duration h: 48 - Notes: Daphnia magna

Endpoint: EL50

- Species: Crustacea <= 10 mg/kg/d - Duration h: 48 - Notes: Daphnia magna

Endpoint: LL50

- Species: Fish >= 2 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss

Endpoint: LL50

- Species: Fish < 5 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss

Endpoint: NOELR - Species: Algae = 2.5 mg/l - Duration h: 72 - Notes: Pseudokirchnerella subcapitata

Endpoint: EL50

Safety Data Sheet

Diestone SR

- Species: Algae = 11 mg/l - Duration h: 72 - Notes: Pseudokirchnerella subcapitata
ethyl (S)-2-hydroxypropionate; ethyl L-lactate; ethyl-(S)-lactate - CAS: 687-47-8

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae > 10 mg/l - Duration h: 70 - Notes: Pseudokirchneriella subcapitata

Endpoint: EC50 - Species: Algae = 3500 mg/l - Duration h: 72 - Notes: Raphidocelis subcapitata, OECD 201

Endpoint: LC50 - Species: Fish = 32 mg/l - Duration h: 96 - Notes: Pimephales promelas

Endpoint: LC50 - Species: Fish = 320 mg/l - Duration h: 96 - Notes: Danio rerio ; OECD 203

b) Aquatic chronic toxicity:

Endpoint: EC50 - Species: Aquatic invertebrates = 683 mg/l - Duration h: 48 - Notes: Daphnia magna ; OECD 202

Persistence and degradability

HYDROCARBONS, C10, AROMATICS, <1% NAPHTHALENE

Biodegradability: Readily biodegradable - Duration: 28 days - %: 50%

ethyl (S)-2-hydroxypropionate; ethyl L-lactate; ethyl-(S)-lactate - CAS: 687-47-8

Biodegradability: Readily biodegradable

naphthalene - CAS: 91-20-3

Biodegradability: Biodegradability rate - Duration: 28 days - %: 50

Bioaccumulative potential

ethyl (S)-2-hydroxypropionate; ethyl L-lactate; ethyl-(S)-lactate - CAS: 687-47-8

Log Pow 0.31

Mobility in soil

N.A.

Other adverse effects

No harmful effects expected.

13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION



UN number

ADR-UN Number: 1993

DOT number: UN1993

IATA-UN Number: 1993

IMDG-UN Number: 1993

UN proper shipping name

ADR-Shipping Name: FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C10, AROMATICS, <1% NAPHTHALENE, ethyl

Safety Data Sheet

Diestone SR

(S)-2-hydroxypropionate; ethyl L-lactate; ethyl-(S)-lactate)

DOT-Shipping Name: Flammable liquids, n.o.s.(ETHYL L-LACTATE)(ETHYL L-LACTATE, HYDROCARBONS, C10, AROMATICS,<1% NAPHTHALENE)

IATA-Shipping Name: FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C10, AROMATICS,<1% NAPHTHALENE, ethyl

(S)-2-hydroxypropionate; ethyl L-lactate; ethyl-(S)-lactate)
IMDG-Shipping Name: FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C10, AROMATICS,<1% NAPHTHALENE, ethyl
(S)-2-hydroxypropionate; ethyl L-lactate; ethyl-(S)-lactate)

Transport hazard class(es)

ADR-Class: 3
DOT Hazard Class: 3
ADR - Hazard identification number: 30
IATA-Class: 3
IATA-Label: 3
IMDG-Class: 3

Packing group

ADR-Packing Group: III
DOT Packing group: III
IATA-Packing group: III
IMDG-Packing group: III

Environmental hazards

ADR-Environmental Pollutant: Yes
IMDG-Marine pollutant: Yes
Most important toxic component: HYDROCARBONS, C10, AROMATICS,<1% NAPHTHALENE

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

N.A.

Special precautions

DOT Special provisions: B1, B52, IB3, T4, TP1, TP29
DOT Labels: 3
ADR-Subsidiary hazards: -
ADR-S.P.: 274 601
ADR-Transport category (Tunnel restriction code): 3 (D/E)
IATA-Passenger Aircraft: 355
IATA-Subsidiary hazards: -
IATA-Cargo Aircraft: 366
IATA-S.P.: A3
IATA-ERG: 3L
IMDG-EmS: F-E , S-E
IMDG-Subsidiary hazards: -
IMDG-Stowage and handling: Category A
IMDG-Segregation: -
Q.L.: 5L

Safety Data Sheet

Diestone SR

Q.E.: E1

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory: all the components are listed on the TSCA inventory or are not required to be listed on the TSCA.

TSCA sections for substances listed in section 3:

HYDROCARBONS, C10, AROMATICS, <1% NAPHTHALENE is listed in TSCA Section 8b
ethyl (S)-2-hydroxypropionate; ethyl L-lactate; ethyl-(S)-lactate is listed in TSCA Section 8b
naphthalene is listed in TSCA Section 8d HSDR, Section 8b, Section 8a - PAIR.

SARA - Superfund Amendments and Reauthorization Act

Section 302 Extremely Hazardous Substances: no substances listed.

Section 304 Hazardous substances: naphthalene.

Section 313 Toxic chemical list: naphthalene.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA: naphthalene - Reportable quantity: 100 pounds.

Reportable quantity for mixture: 25188.91688 pounds.

CAA - Clean Air Act

CAA listed substances:

naphthalene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON.

CWA - Clean Water Act

CWA listed substances:

naphthalene is listed in CWA Section 304, Section 307, Section 311, CWA Priority
Pollutants.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

naphthalene - Listed as carcinogen.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

naphthalene.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

naphthalene.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

naphthalene.

The following substance(s) in this product has/have an identification by CAS number either in countries not affected by the REACH regulation or in regulations not yet updated to reflect the new naming convention for hydrocarbon solvents:

HYDROCARBONS, C10, AROMATICS, <1% NAPHTHALENE (CAS: 64742-94-5)

Safety Data Sheet

Diestone SR

16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

- H304 May be fatal if swallowed and enters airways.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- H226 Flammable liquid and vapour.
- H335 May cause respiratory irritation.
- H318 Causes serious eye damage.
- H351 Suspected of causing cancer.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H302 Harmful if swallowed.

According to TSCA section 3(2)(B)(i) : a hydrated form of a chemical substance is considered a mixture of the corresponding anhydrous form and water.

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

- | | |
|-----------|--|
| ADR: | European Agreement concerning the International Carriage of Dangerous Goods by Road. |
| ATE: | Acute Toxicity Estimate |
| ATEmix: | Acute toxicity Estimate (Mixtures) |
| CAS: | Chemical Abstracts Service (division of the American Chemical Society). |
| CLP: | Classification, Labeling, Packaging. |
| DNEL: | Derived No Effect Level. |
| EINECS: | European Inventory of Existing Commercial Chemical Substances. |
| GHS: | Globally Harmonized System of Classification and Labeling of Chemicals. |
| HMIS: | Hazardous Materials Identification System |
| IARC: | International Agency for Research on Cancer |
| IATA: | International Air Transport Association. |
| IATA-DGR: | Dangerous Goods Regulation by the "International Air Transport Association" (IATA). |
| ICAO: | International Civil Aviation Organization. |
| ICAO-TI: | Technical Instructions by the "International Civil Aviation Organization" (ICAO). |
| IMDG: | International Maritime Code for Dangerous Goods. |
| INCI: | International Nomenclature of Cosmetic Ingredients. |
| KSt: | Explosion coefficient. |
| LC50: | Lethal concentration, for 50 percent of test population. |

Safety Data Sheet

Diestone SR

LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average

Safety Data Sheet date: 1/15/2024, version 1