

FUN NG VERT 40462 P.A

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/08/2019

 1.5
 02/17/2020
 102000050548
 Date of first issue: 06/03/2017

SECTION 1. IDENTIFICATION

1.1 Product identifier

Trade name : FUN NG VERT 40462 P.A

Identification of the article : 2018596

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mix-

ture

Industrial paint

1.3 Relevant Parties

Supplier

Company : Dysol, Inc. dba Socomore
Address : 791 Westport Parkway
Fort Worth, TX 76177 USA

FOIL WOILII, IX 70177

Telephone : 1-817-335-1826

Email : techsupport-na@socomore.com

Website : www.socomore.com / store.socomore.com

Manufacturer

Company : MÄDER AERO

Address : Rue Jean Baptiste Réveillon 2

FR - 61300 L'AIGLE

Telephone : +33320127950

Email : products-safety.mader-france@mader-group.com

1.4 Emergency telephone number

Emergency telephone

number

CHEMTEL: I+1-813-248-0585 (International); 1-800-255-3924 (USA)

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitisation : Category 1

Reproductive toxicity : Category 2

Specific target organ toxicity

- single exposure

Category 3 (Respiratory system)

Specific target organ toxicity

- repeated exposure

Category 2



FUN NG VERT 40462 P.A

Version Revision Date: SDS Number: Date of last issue: 02/08/2019 1.5 02/17/2020 102000050548 Date of first issue: 06/03/2017

GHS label elements

Hazard pictograms







Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or re-

peated exposure.

Precautionary statements

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting equipment

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge. P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.



FUN NG VERT 40462 P.A

Version Revision Date: SDS Number: Date of last issue: 02/08/2019 1.5 02/17/2020 102000050548 Date of first issue: 06/03/2017

P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alco-

hol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Industrial paint

Components

Chemical name	CAS-No.	Concentration (% w/w)
Xylene	1330-20-7	>= 20 - < 30
	25068-38-6	>= 20 - < 30
(propane-2,2-diyl)diphenol]		
2-Butoxyethanol	111-76-2	>= 5 - < 10
Ethylbenzene	100-41-4	>= 5 - < 10
1-Butanol	71-36-3	>= 1 - < 5
Zinc oxide	1314-13-2	>= 1 - < 5
Titanium dioxide	13463-67-7	>= 0.1 - < 1
Toluene	108-88-3	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.



FUN NG VERT 40462 P.A

Version Revision Date: SDS Number: Date of last issue: 02/08/2019
1.5 02/17/2020 102000050548 Date of first issue: 06/03/2017

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation.

Suspected of damaging the unborn child.

May cause damage to organs through prolonged or repeated

exposure.

Notes to physician : No information available.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical High volume water jet

Unsuitable extinguishing me-

dıa

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod-

ucts

No hazardous combustion products are known

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Remove all sources of ignition.

Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas. No conditions to be specially mentioned.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Contain spillage, and then collect with non-combustible absor-

bent material, (e.g. sand, earth, diatomaceous earth,



FUN NG VERT 40462 P.A

Version Revision Date: SDS Number: Date of last issue: 02/08/2019 1.5 02/17/2020 102000050548 Date of first issue: 06/03/2017

vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Do not spray on a naked flame or any incandescent material.

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Keep away from open flames, hot surfaces and sources of ig-

nition.

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the appli-

cation area.

Take precautionary measures against static discharges.

Provide sufficient air exchange and/or exhaust in work rooms.

Open drum carefully as content may be under pressure.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage

No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age stability

No decomposition if stored and applied as directed.



FUN NG VERT 40462 P.A

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/08/2019

 1.5
 02/17/2020
 102000050548
 Date of first issue: 06/03/2017

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of ex-	Control parameters / Permissible	Basis
		posure)	concentration	
Xylene	1330-20-7	TWA	100 ppm	OSHA Z-1
			435 mg/m3	
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		STEL	150 ppm	OSHA P0
			655 mg/m3	
		TWA	100 ppm 435 mg/m3	OSHA P0
2-Butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
,		TWA	5 ppm 24 mg/m3	NIOSH REL
		TWA	50 ppm 240 mg/m3	OSHA Z-1
		TWA	25 ppm 120 mg/m3	OSHA P0
Ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
•		TWA	100 ppm	NIOSH REL
			435 mg/m3	
		ST	125 ppm 545 mg/m3	NIOSH REL
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA P0
		STEL	125 ppm 545 mg/m3	OSHA P0
1-Butanol	71-36-3	TWA	20 ppm	ACGIH
		С	50 ppm 150 mg/m3	NIOSH REL
		TWA	100 ppm	OSHA Z-1
			300 mg/m3	
		С	50 ppm 150 mg/m3	OSHA P0
Zinc oxide	1314-13-2	TWA (Respirable particulate matter)	2 mg/m3	ACGIH
		STEL (Respirable particulate matter)	10 mg/m3	ACGIH
		TWA (Dust)	5 mg/m3	NIOSH REL
		TWA (Fumes)	5 mg/m3	NIOSH REL
		ST (Fumes)	10 mg/m3	NIOSH REL
		C (Dust)	15 mg/m3	NIOSH REL



FUN NG VERT 40462 P.A

ersion	Revision Date:	SDS Number:		issue: 02/08/2019	ĺ
.5	02/17/2020	102000050548	TWA (total	issue: 06/03/2017 15 mg/m3	OSHA Z-1
			dust)	To mg/mo	0011/12 1
			TWA (respir-	5 mg/m3	OSHA Z-1
			able fraction)	o mg/mo	0011/12 1
			TWA	5 mg/m3	OSHA Z-1
			(Fumes)	o mg/mo	0011/12 1
			TWA (Total	10 mg/m3	OSHA P0
			dust)	10 mg/mo	0011/110
			TWA (respir-	5 mg/m3	OSHA P0
			able dust	o mg/me	
			fraction)		
			TWA	5 mg/m3	OSHA P0
			(Fumes)	g	
			STEL	10 mg/m3	OSHA P0
			(Fumes)		
Titan	ium dioxide	13463-67-7	TWA (total	15 mg/m3	OSHA Z-1
			dust) `		
			TWÁ (Total	10 mg/m3	OSHA P0
			dust) `		
			TWÁ	10 mg/m3	ACGIH
				(Titanium dioxide)	
Tolue	ene	108-88-3	TWA	20 ppm	ACGIH
			TWA	100 ppm	NIOSH REL
				375 mg/m3	
			ST	150 ppm	NIOSH REL
				560 mg/m3	
			TWA	200 ppm	OSHA Z-2
			CEIL	300 ppm	OSHA Z-2
			Peak	500 ppm	OSHA Z-2
				(10 minutes)	
			TWA	100 ppm	OSHA P0
				375 mg/m3	
			STEL	150 ppm	OSHA P0
				560 mg/m3	



FUN NG VERT 40462 P.A

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/08/2019

 1.5
 02/17/2020
 102000050548
 Date of first issue: 06/03/2017

Biological occupational exposure limits

Components	CAS-No.	Control pa- rameters	Biological specimen	Sam- pling time	Permissible concentration	Basis
Xylene	1330-20-7	Methylhip- puric acids	Urine	End of shift (As soon as possible after ex- posure ceases)	1.5 g/g creatinine	ACGIH BEI
2-Butoxyethanol	111-76-2	Butoxyace- tic acid (BAA)	Urine	End of shift (As soon as possible after ex- posure ceases)	200 mg/g Creatinine	ACGIH BEI
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after ex- posure ceases)	0.03 mg/l	ACGIH BEI

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an ap-

proved filter.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.



FUN NG VERT 40462 P.A

Version Revision Date: SDS Number: Date of last issue: 02/08/2019

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES Date of first issue: 06/03/2017

Appearance : liquid

Colour : green

Odour : solvent-like

pH : Not applicable

Melting point/freezing point : Not applicable

Boiling point/boiling range : $> 97 \, ^{\circ}\text{F} / > 36 \, ^{\circ}\text{C}$

Flash point : ca. 73 °F / 23 °C

Evaporation rate : No data available

Self-ignition : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : < 1,000 hPa (122 °F / 50 °C)

Relative vapour density : No data available

Density : ca. 1.22 g/cm3 (73 °F / 23 °C)

Solubility(ies)

Water solubility : immiscible

Partition coefficient: n-oc-

tanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : Not applicable

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.6 mm2/s (104 °F / 40 °C)

Explosive properties : No data available

Oxidizing properties : No data available



FUN NG VERT 40462 P.A

Revision Date: Version SDS Number: Date of last issue: 02/08/2019 Date of first issue: 06/03/2017

SECTION 10. STABILITY AND REACTIVITY 50548

No decomposition if stored and applied as directed. Reactivity No decomposition if stored and applied as directed. Chemical stability

Possibility of hazardous reac-

tions

No dangerous reaction known under conditions of normal use.

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid Heat, flames and sparks. Incompatible materials Strong oxidizing agents

Hazardous decomposition

products

Stable under recommended storage conditions.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: 4,545 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 26.03 mg/l

> Exposure time: 4 h Test atmosphere: vapour Method: Calculation method

Acute toxicity estimate: 2,977 mg/kg Acute dermal toxicity

Method: Calculation method

Components:

Zinc oxide:

Acute oral toxicity : LD50 (Rat): > 15,000 mg/kg

LD50 Oral (Mouse): 7,950 mg/kg

LC50 (Rat): > 5.7 mg/l Acute inhalation toxicity

Exposure time: 4 h Test atmosphere: vapour

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks May cause irreversible eye damage.



FUN NG VERT 40462 P.A

Version Revision Date: SDS Number: Date of last issue: 02/08/2019 1.5 02/17/2020 102000050548 Date of first issue: 06/03/2017

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC Group 2B: Possibly carcinogenic to humans

Ethylbenzene 100-41-4

Group 2B: Possibly carcinogenic to humans

Titanium dioxide 13463-67-7

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Suspected of damaging the unborn child.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available



FUN NG VERT 40462 P.A

Version Revision Date: SDS Number: Date of last issue: 02/08/2019 1.5 02/17/2020 102000050548 Date of first issue: 06/03/2017

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Pro-

tection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1263 Proper shipping name : PAINT

(,)

366

Class : 3 Packing group : III Labels : 3

IATA-DGR

UN/ID No. : UN 1263
Proper shipping name : PAINT

(ethylbenzene, 2-butoxyethanol; ethylene glycol monobutyl

ether butyl cellosolve)

Class : 3 Packing group : III

Labels : Flammable Liquids

Packing instruction (cargo

aircraft)



FUN NG VERT 40462 P.A

Version Revision Date: 1.5 Packing instruction (passen-ger aircraft) SDS Number: Date of last issue: 02/08/2019 10200050548 Date of first issue: 06/03/2017

IMDG-Code

UN number UN 1263 Proper shipping name **PAINT**

> (ethylbenzene, 2-butoxyethanol; ethylene glycol monobutyl ether butyl cellosolve)(, trizinc bis(orthophosphate), zinc ox-

ide)

Class 3 Ш Packing group 3 Labels **EmS Code** F-E, <u>S-E</u> Marine pollutant yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

: UN 1263 UN/ID/NA number Proper shipping name **PAINT**

(ethylbenzene, 2-butoxyethanol; ethylene glycol monobutyl

ether butyl cellosolve)

Class 3 Ш Packing group

Labels FLAMMABLE LIQUID

ERG Code

Marine pollutant yes(trizinc bis(orthophosphate), zinc oxide)

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Xylene	1330-20-7	100	359
Xylene	1330-20-7	100	100 (F003)
Ethylbenzene	100-41-4	100	100 (F003)
1-Butanol	71-36-3	100	100 (F003)
Methyl isobutyl ketone	108-10-1	100	100 (F003)
Toluene	108-88-3	100	100 (F005)
2-Methyl-1-propanol	78-83-1	100	100 (F005)
2-Butanone	78-93-3	100	100 (F005)
2-Butanone	78-93-3	5,000	5,000 (D035)



FUN NG VERT 40462 P.A

Version Revision Date: SDS Number: Date of last issue: 02/08/2019
1.5 SARA 304/EM/2019 Hazardo182909859548s RepoRate Guatintes e: 06/03/2017

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards Flammable (gases, aerosols, liquids, or solids)

Respiratory or skin sensitisation

Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

Zinc(II) phos- 7779-90-0 >= 20 - < 30 % phate

2-Butoxyethanol 111-76-2 >= 5 - < 10 %

Ethylbenzene 100-41-4 >= 5 - < 10 %

1-Butanol 71-36-3 >= 1 - < 5 %

Zinc oxide 1314-13-2 >= 1 - < 5 %

1,3,5-triazine- 24468-28-8 >= 1 - < 5 % 2,4,6(1H,3H,5H)-

trione, zinc salt

Zinc phosphate 7779-90-0 < 0.1 %

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

Xylene 1330-20-7 >= 20 - < 30 % Ethylbenzene 100-41-4 >= 5 - < 10 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

Xylene1330-20-7>= 20 - < 30 %2-Butoxyethanol111-76-2>= 5 - < 10 %Ethylbenzene100-41-4>= 5 - < 10 %1-Butanol71-36-3>= 1 - < 5 %



FUN NG VERT 40462 P.A

Version Revision Date: SDS Number: Date of last issue: 02/08/2019
1.5 Clean Ward 7/2020 102000050548 Date of first issue: 06/03/2017

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Ta-

ble 116.4A:

 Xylene
 1330-20-7
 >= 20 - < 30 %</td>

 Ethylbenzene
 100-41-4
 >= 5 - < 10 %</td>

 Toluene
 108-88-3
 >= 0.1 - < 1 %</td>

 Butyl acetate
 123-86-4
 >= 0 - < 0.1 %</td>

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

117.3:

 Xylene
 1330-20-7
 >= 20 - < 30 %</td>

 Ethylbenzene
 100-41-4
 >= 5 - < 10 %</td>

 Toluene
 108-88-3
 >= 0.1 - < 1 %</td>

 Butyl acetate
 123-86-4
 >= 0 - < 0.1 %</td>

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section

307

Zinc(II) phosphate7779-90-0>= 20 - < 30 %Ethylbenzene100-41-4>= 5 - < 10 %Zinc oxide1314-13-2>= 1 - < 5 %1,3,5-triazine-24468-28-8>= 1 - < 5 %

2,4,6(1H,3H,5H)-trione,

zinc salt

This product contains the following priority pollutants related to the U.S. Clean Water Act:

Ethylbenzene 100-41-4 >= 5 - < 10 %

US State Regulations

Massachusetts Right To Know

 Xylene
 1330-20-7

 2-Butoxyethanol
 111-76-2

 Ethylbenzene
 100-41-4

 1-Butanol
 71-36-3

 Zinc oxide
 1314-13-2

 Quartz
 14808-60-7

Pennsylvania Right To Know

Xylene 1330-20-7 Zinc(II) phosphate 7779-90-0 Poly[2-(chloromethyl)oxirane-alt-4,4'-(propane-2,2-diyl)diphe-25068-38-6 nol] 2-Butoxyethanol 111-76-2 Ethylbenzene 100-41-4 1-Butanol 71-36-3 Zinc oxide 1314-13-2 1,3,5-triazine-2,4,6(1H,3H,5H)-trione, zinc salt 24468-28-8 Toluene 108-88-3 Butyl acetate 123-86-4 2-Methyl-1-propanol 78-83-1 Zinc phosphate 7779-90-0 2-Butanone 78-93-3



FUN NG VERT 40462 P.A

Version Revision Date: SDS Number: Date of last issue: 02/08/2019
1.5 Maine CN2/11/20220f High Contects 00050548 Date of first issue: 06/03/2017

Toluene 108-88-3 Quartz 14808-60-7

The following chemicals are listed as Maine Chemicals of High Concern:

Maine Chemicals of High Concern

Toluene 108-88-3 Quartz 14808-60-7

Vermont Chemicals of High Concern

 Ethylbenzene
 100-41-4

 Toluene
 108-88-3

 2-Butanone
 78-93-3

Washington Chemicals of High Concern

 Ethylbenzene
 100-41-4

 Toluene
 108-88-3

 2-Butanone
 78-93-3

California Prop. 65

WARNING: This product can expose you to chemicals including Ethylbenzene, Titanium dioxide, Methyl isobutyl ketone, Carbon black, Quartz, Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified, which is/are known to the State of California to cause cancer, and Toluene, Methyl isobutyl ketone, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Xylene	1330-20-7
Zinc(II) phosphate	7779-90-0
2-Butoxyethanol	111-76-2
Ethylbenzene	100-41-4
1-Butanol	71-36-3
Zinc oxide	1314-13-2
1,3,5-triazine-2,4,6(1H,3H,5H)-trione, zinc salt	24468-28-8

California Permissible Exposure Limits for Chemical Contaminants

Xylene	1330-20-7
2-Butoxyethanol	111-76-2
Ethylbenzene	100-41-4
1-Butanol	71-36-3
Zinc oxide	1314-13-2

The components of this product are reported in the following inventories:

TSCA : Substance(s) not listed on TSCA inventory

: This product contains the following components that are not

on the Canadian DSL nor NDSL.



FUN NG VERT 40462 P.A

Version 1.5 DSL

Revision Date: 02/17/2020

SDS Number: 102000050548

Date of last issue: 02/08/2019 Date of first issue: 06/03/2017

no hazardous substance

polyamine amide salt

mix urea-aldehyde

polyurethane, non hazardous

TSCA list


No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-2 : USA. Occupational Exposure Limits (OSHA) - Table Z-2

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit



FUN NG VERT 40462 P.A

SDS Number: Date of last issue: 02/08/2019 10200065699hted average concentration 10/09/2019 10-hour workday during a 40-hour workweek Version Revision Date: 1.5 NIOSH RE/17/2020 NIOSH REL / ST STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday Ceiling value not be exceeded at any time. NIOSH REL / C OSHA P0 / TWA 8-hour time weighted average Short-term exposure limit OSHA P0 / STEL OSHA P0 / C Ceiling limit OSHA Z-1 / TWA 8-hour time weighted average 8-hour time weighted average OSHA Z-2 / TWA OSHA Z-2 / CEIL Acceptable ceiling concentration Acceptable maximum peak above the acceptable ceiling con-OSHA Z-2 / Peak centration for an 8-hr shift

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS -Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 02/17/2020



FUN NG VERT 40462 P.A

Version Revision Date: SDS Number: Date of last issue: 02/08/2019
1.5 The information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN