

## Safety Data Sheet

### MEK WIPES - P29101-NA

Safety Data Sheet dated 8/28/2018, version 2

#### 1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: MEK WIPES

Other means of identification:

SDS code: P29101-NA

Recommended use of the chemical and restrictions on use

Recommended use:

Solvent

Cleaner

Industrial uses

Professional uses

Restrictions on use:

No uses advised against are identified.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company:

Dysol Inc. - 791 Westport Parkway - Fort Worth, TX 76177 / Phone: 1-817-335-1826 /  
csr-na@socomore.com/ Fax Number: 817-335-2405

Distributor: SOCOMORE S.A.S. - Zone Industrielle du Prat - CS 23707 - 56037 VANNES  
CEDEX - France - Tel : +33 (0)2 97 43 76 83 - Fax : +33 (0)2 97 54 20 26

Distributor: Socomore Ltd - 5, Coe Avenue - Loughborough - Leicestershire - LE11 4SE - UK  
- Tel: +44 1509 262040 - Fax: +44 1509 262046

Distributor: Socomore Iberia - Calle Diputacio, 260 - 08007 Barcelona - Espana - Tel: +34 917  
693 962 - Fax: +34 902 908 966

Distributor: MagChem Inc. 1271, rue Ampere, suite 101, Boucherville, QC, J4B 5Z5 Canada -  
Tel: 1-450 641 8500 - Fax: 1-450 655 1717

Distributor: Socomore GmbH - c/o MAZARS GmbH - Theodor-Stern-Kai 1 - 60596 Frankfurt  
am Main - Deutschland - Tel: +49 (0)89 20 70 28 83 - Fax: +49 (0) 89 88 91 98 16

Distributor: Socomore Trading Shanghai - 355 East Kang Qiao Road - Kang Qiao Industrial  
Zone - Pudong - 201315 Shanghai - Tel: 862158131133 - Fax: 862158131933

Dystrybutor : SOCOMORE SPzoo - Ul. Piekna 18, 00-549 Warszawa Polska - Tel : +48 608  
454 114 - Fax : +48 (22) 621 61 09

Competent person responsible for the safety data sheet:





techdirsocomore@socomore.com

Emergency phone number

CHEMTEL: 1-800-255-3924 (USA) / CANUTEC: 1-613-996-6666 (CANADA)

#### 2. HAZARD(S) IDENTIFICATION

Classification of the chemical

-  Danger, Flam. Liq. 2, Highly flammable liquid and vapour.
-  Warning, Skin Irrit. 2, Causes skin irritation.
-  Warning, Eye Irrit. 2A, Causes serious eye irritation.
-  Warning, STOT SE 3, May cause drowsiness or dizziness.

## Safety Data Sheet

### MEK WIPES - P29101-NA

Label elements

Hazard pictograms:



Danger

Hazard statements:

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P210 Keep away from heat - No smoking.

P240 Ground container and receiving equipment.

P241 Use explosion-proof electrical equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing vapours.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves and eye/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER if you feel unwell.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire, use a CO2 fire extinguisher to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None.

---

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Identification of the substance:

MSDS code: P29101-NA

## Safety Data Sheet

### MEK WIPES - P29101-NA

>= 90% BUTANONE;ETHYL METHYL KETONE

REACH No.: 01-2119457290-43, Index number: 606-002-00-3, CAS: 78-93-3, EC: 201-159-0



A.2/2 Skin Irrit. 2 H315



B.6/2 Flam. Liq. 2 H225



A.3/2A Eye Irrit. 2A H319



A.8/3 STOT SE 3 H336

Mixtures

N.A.

---

#### 4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting. Obtain a medical examination.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

Burning sensation.

Repeated exposure may cause skin dryness or cracking.

Tumor.

Blurred vision.

Tearing.

Swollen eyelids.

Itching.

Vapours may cause drowsiness and dizziness.

Temporary burning sensation of nose and throat.

Cough

Difficulty breathing.

Indication of immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

Call a doctor or poison control center for further instructions.

---

#### 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

In case of fire, use a CO2 fire extinguisher to extinguish.

Unsuitable extinguishing media:

None in particular.

## Safety Data Sheet

### MEK WIPES - P29101-NA

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties: N.A.

Oxidizing properties: N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Remove persons to safety.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

Methods and materials for containment and cleaning up

Wash with plenty of water.

---

#### 7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not use on extensive surface areas in premises where there are occupants.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Avoid accumulating electrostatic charge.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

Storage temperature:

Store at ambient temperature.

---

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

BUTANONE;ETHYL METHYL KETONE - CAS: 78-93-3

- OEL Type: National - TWA: 600 mg/m<sup>3</sup>, 200 ppm - STEL: 900 mg/m<sup>3</sup>, 300 ppm –

## Safety Data Sheet

### MEK WIPES - P29101-NA

Notes: France VLEC

- OEL Type: EU - TWA(8h): 600 mg/m<sup>3</sup>, 200 ppm - STEL: 900 mg/m<sup>3</sup>, 300 ppm  
 - OEL Type: ACGIH - TWA(8h): 200 ppm - STEL: 300 ppm - Notes: BEI - URT irr, CNS and PNS impair

- OEL Type: National - TWA: 600 mg/m<sup>3</sup>, 200 ppm - Notes: AGW, Germany

DNEL Exposure Limit Values

BUTANONE;ETHYL METHYL KETONE - CAS: 78-93-3

Worker Industry: 1161 mg/kg - Consumer: 412 mg/kg - Exposure: Human Dermal - Frequency: Short Term (acute) - Notes: 1 day

Worker Industry: 600 mg/m<sup>3</sup> - Consumer: 106 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term (acute)

Consumer: 31 mg/kg - Exposure: Human Oral - Frequency: Short Term (acute)

PNEC Exposure Limit Values

BUTANONE;ETHYL METHYL KETONE - CAS: 78-93-3

Target: Fresh Water - Value: 55.8 mg/l

Target: Marine water - Value: 55.8 mg/l

Target: Freshwater sediments - Value: 284.74 mg/kg

Target: Marine water sediments - Value: 287.7 mg/kg

Target: Soil (agricultural) - Value: 22.5 mg/kg

Appropriate engineering controls:

None

Individual protection measures

Eye protection:

Safety goggles (EN 166)

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Chemical protection clothing. (type 3 - EN14605)

Chemical protection clothing. (type 5 - EN13982-1)

Chemical protection clothing. (type 6 - EN13034)

Protection for hands:

Suitable gloves type: NF EN374

PVA (Polyvinyl alcohol).

Butyl rubber (isobutylene-isoprene copolymer)

Respiratory protection:

Use adequate protective respiratory equipment.

Filtering Half-face mask (NF EN 149), class FFP1

Mask with filter "A1" , brown colour (NF EN14387)

Thermal Hazards:

None

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Value	Method:	Notes
Appearance and colour:	Liquid coated on wipes	--	--
Odour:	N.A.	--	--
Odour threshold:	N.A.	--	--
pH:	N.A.	--	--
Melting point / freezing point:	N.A.	--	--
Initial boiling point and boiling range:	77 79 81 °C / 172 175 178 °F	--	--
Flash Point (°F):	28° F (TCC)	--	--

## Safety Data Sheet

### MEK WIPES - P29101-NA

Flash point (°C):	-2 °C (TCC)	--	--
Evaporation rate:	3.6	--	--
Solid/gas flammability:	Not Relevant	--	--
Upper/lower flammability or explosive limits:	1.8	--	--
Vapour pressure:	70	--	--
Vapour density:	2.5	--	--
Relative density:	0.805	--	--
Solubility in water:	N.A.	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient (n-octanol/water):	N.A.	--	--
Auto-ignition temperature:	515 °C / 960 °F	--	--
Decomposition temperature:	N.A.	--	--
Viscosity:	N.A.	--	--
Explosive properties:	N.A.	--	--
Oxidizing properties:	N.A.	--	--

#### 9.2. Other information

Properties	Value	Method:	Notes
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	N.A.	--	--

## 10. STABILITY AND REACTIVITY

#### Reactivity

Vapours may form an explosive mixture with air.

#### Chemical stability

It may generate dangerous reactions (See subsections below)

#### Possibility of hazardous reactions

None

#### Conditions to avoid

Avoid accumulating electrostatic charge.

#### Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

#### Hazardous decomposition products

None.

## 11. TOXICOLOGICAL INFORMATION

#### Information on toxicological effects

#### Toxicological information of the substance:

N.A.

#### Substance(s) listed on the NTP report on Carcinogens:

No.

#### Substance(s) listed on the IARC Monographs:

None.

**Safety Data Sheet**  
**MEK WIPES - P29101-NA**

Substance(s) listed as OSHA Carcinogen(s):

No.

Substance(s) listed as NIOSH Carcinogen(s):

No.

**12. ECOLOGICAL INFORMATION**

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

BUTANONE;ETHYL METHYL KETONE - CAS: 78-93-3

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 13 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss

Endpoint: EC50 - Species: Algae > 100 mg/l - Duration h: 168 - Notes: Desmodesmus subspicatus

Persistence and degradability

BUTANONE;ETHYL METHYL KETONE - CAS: 78-93-3

Biodegradability: Readily biodegradable - Test: N.A. - Duration: 28 days - %: 98 - Notes: aerobic

Bioaccumulative potential

BUTANONE;ETHYL METHYL KETONE - CAS: 78-93-3

Log Pow - Test: N.A. 0.3 - Duration: N.A. - Notes: N.A.

Log Kow - Test: N.A. 0.3 - Duration: N.A. - Notes: N.A.

Mobility in soil

N.A.

Other adverse effects

No harmful effects expected.

**13. DISPOSAL CONSIDERATIONS**

Waste treatment and disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

**14. TRANSPORT INFORMATION**



UN number

ADR-UN Number: 3175

DOT number: UN3175

IATA-UN Number: 3175

IMDG-UN Number: 3175

UN proper shipping name

ADR-Shipping Name: SOLIDS or mixtures of solids (such as preparations and wastes) CONTAINING FLAMMABLE LIQUID, N.O.S. having a flash-point up to 60 °C (butanone; ethyl methyl ketone)

DOT-Shipping Name: SOLIDS or mixtures of solids (such as preparations and wastes) CONTAINING FLAMMABLE LIQUID, N.O.S. having a flash-point up to 60 °C (butanone; ethyl methyl ketone)

## Safety Data Sheet

### MEK WIPES - P29101-NA

IATA-Shipping Name:	SOLIDS or mixtures of solids (such as preparations and wastes) CONTAINING FLAMMABLE LIQUID, N.O.S. having a flash-point up to 60 °C (butanone; ethyl methyl ketone)
IMDG-Shipping Name:	SOLIDS or mixtures of solids (such as preparations and wastes) CONTAINING FLAMMABLE LIQUID, N.O.S. having a flash-point up to 60 °C (butanone; ethyl methyl ketone)
Transport hazard class(es)	
ADR-Class:	4.1
DOT Hazard Class:	4.1
ADR - Hazard identification number:	40
IATA-Class:	4.1
IATA-Label:	4.1
IMDG-Class:	4.1
Packing group	
ADR-Packing Group:	II
DOT Packing group:	II
IATA-Packing group:	II
IMDG-Packing group:	II
Environmental hazards	
ADR-Environmental Pollutant:	No
IMDG-Marine pollutant:	No
Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)	N.A.
Special precautions	
DOT Special provisions:	47, IB6, IP2, T3, TP33
DOT Labels:	4.1
ADR-Subsidiary risks:	-
ADR-S.P.:	216 274 601
ADR-Transport category (Tunnel restriction code):	(E)
IATA-Passenger Aircraft:	445
IATA-Subsidiary risks:	-
IATA-Cargo Aircraft:	448
IATA-S.P.:	A46
IATA-ERG:	3L
IMDG-EmS:	F-A , S-I
IMDG-Subsidiary risks:	-
IMDG-Stowage and handling:	Category B
IMDG-Segregation:	-
Q.L.:	1K
Q.E.:	E2

## 15. REGULATORY INFORMATION

### USA - Federal regulations

TSCA - Toxic Substances Control Act

This substance is listed on the TSCA inventory.

TSCA listed substances:

BUTANONE;ETHYL METHYL KETONE is listed in TSCA Section 8b, Section 8d HSDR.

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances: No.

Section 304 - Hazardous substances: Yes.

Section 313 - Toxic chemical list: No.



## Safety Data Sheet

### MEK WIPES - P29101-NA

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act  
Substance(s) listed under CERCLA: BUTANONE;ETHYL METHYL KETONE -  
Reportable quantity: 5000 pounds.

CAA - Clean Air Act

CAA listed substances:

BUTANONE;ETHYL METHYL KETONE is listed in CAA Section 111, Section 112(b) -  
HAP, Section 112(b) - HON.

CWA - Clean Water Act

CWA listed substances:

None.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

None.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

Yes.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

Yes.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

Yes.

The following substance(s) in this product has/have an identification by CAS number  
either in countries not affected by the REACH regulation or in regulations not yet  
updated to reflect the new naming convention for hydrocarbon solvents:

---

## 16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

H315 Causes skin irritation.

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Safety Data Sheet dated 8/28/2018, version 2

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of  
Dangerous Goods by Road.

CAS: Chemical Abstracts Service (division of the American Chemical  
Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GHS: Globally Harmonized System of Classification and Labeling of  
Chemicals.

HMIS: Hazardous Materials Identification System

IARC: International Agency for Research on Cancer

## Safety Data Sheet

### MEK WIPES - P29101-NA

IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average