

- **SOCOMUL A2220 is a formulation which allows to increase the bath's lifetime and enhance its performance while controlling its foaming production.**
- Complies with EC regulation 648/2004.
- Compared to traditional surfactant formulations, SOCOMUL A2220 provides a largest tolerance to oil and grease loads present in the bath while preserving excellent performances.
- Composed of biodegradable surfactants.

## **USES**

Compatible with most alkaline baths; stable from 0 to 100°C (32°C - 212°F) and inert on all surfaces.

## **DIRECTIONS FOR USE**

Current dosage is 0.1 to 1 % for deoxidation baths running at a temperature from 40 to 60°C (104 - 140°F).

Check that the bath is perfectly homogenized after introducing SOCOMUL A2220.

## **TECHNICAL CHARACTERISTICS**

Appearance ..... colourless liquid  
Specific gravity ..... 1(20°C - 68°F)  
pH ..... 7 (undiluted)

## **PRECAUTIONS FOR USE AND STORAGE**

Please refer to the safety data sheet of the product

**This technical data sheet replaces and cancels the previous one.**

The above details have been compiled to the best of our knowledge. They have, however, an indicative value only and we therefore make no warranties and assume no liability in connection with any use of this information, particularly if a third party's rights are affected by the use of our products. The above information has been compiled based upon tests carried out by SOCOMORE. All data is subject to change as Socomore deems appropriate. The data given is not intended to substitute for any testing you must conduct in order to determine the suitability of the product for your particular purposes. Please check your local legislation applicable to the use of this product. Should you need any further information please contact us.