


Approvals and conformities

SAE AMS 3819D Grade A (conformity to technical requirements)

- **Very low linting** (no fibres or particles) - a key criteria in surface preparation operations.
- **High mechanical resistance to tearing and abrasion.**
- **Good solvent absorption capacity** combined with the large wipe size facilitates cleaning of large surface areas.
- **Excellently captures dust and soil.**
- 'Mini-Jumbo' dispenser available for ease of storage and use in workshops.
- **A wide range of pre-saturation solutions are available, including DIESTONE DLS, DIESTONE D. Other solutions are also available,** depending on the application. Please contact us for further information.

Description	Size (cm)	Number of wipes
Pre-cut rolls (wipes folded in 2)	30 x 48	70 / bucket



Different packaging available on demand

USES

For surface preparation prior to painting on painted or unpainted surfaces, metallic or composite materials. Suitable for cleaning riveted and mildly abrasive surfaces. Meets aerospace cleaning requirements prior to painting.

TECHNICAL CHARACTERISTICS

Wipe construction non-woven
 Wipe fabric micro fiber PET / PA
 Weight 80 gr/m²
 Colour white

BENEFITS OF PRESATURATED WIPES

The pre-saturated wipe system provides economical, environmental and safety advantages for users compared with the method of using liquid solvent and cloth. It helps to:

- Standardise cleaning and preparation operations,
- Improve quality and production line performance,
- Reduce the quantity of product consumed,
- Reduce waste:
 - for the same surface, the volume of wipes used is 5 to 10 times less than the volume of traditional cloths,
 - less loose liquids,
- Reduce VOCs (Volatile Organic Compounds) by 65% on average, as targeted by European Legislation
- Improve users' safety:
 - Drastically reduces the quantity of solvent released into the atmosphere
 - No risk of accidental spillage from drums full of flammable liquids (fire hazard)
 - Pre-saturated wipes are easy to use, handle and store compared to cloths and solvent drums.

PRECAUTIONS FOR USE AND STORAGE

For more information regarding the danger of the product, please consult the safety data sheet of the relevant saturation product, according to local regulation.

For professional use only.

This technical data sheet replaces and cancels the previous one.

The above details have been compiled to the best of our knowledge. They have, however, an indicative value only and we therefore make no warranties and assume no liability in connection with any use of this information, particularly if a third party's rights are affected by the use of our products. The above information has been compiled based upon tests carried out by SOCOMORE. All data is subject to change as SOCOMORE deems appropriate. The data given is not intended to substitute for any testing you must conduct in order to determine the suitability of the product for your particular purposes. Pictures are not contractual. Please check your local legislation applicable to the use of this product. Should you need any further information please contact us.