

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSTRIP A4512

Regulation (EU) n. 2020/878

Safety Data Sheet date: 10/8/2022, version 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: SOCOSTRIP A4512
SDS code: P54512
UFI: 5AW0-G37A-925M-MJ4Q

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Solvent

Industrial uses

Uses advised against:

No uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Manufacturers:

Socomore SASU

Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France

Tel : +33 (0)2 97 43 76 83 - Fax : +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax +353 21 4889923 / ireland@socomore.com

Distributors:

Socomore SASU

Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France

Tel : +33 (0)2 97 43 76 83 - Fax : +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax +353 21 4889923 / ireland@socomore.com

Competent person responsible for the safety data sheet:

techdirsocomore@socomore.com

1.4. Emergency telephone number

France : ORFILA (INRS) +33 (0)1 45 42 59 59

International : CHEMTEL +1-813-248-0585.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

- ⚠ Warning, Met. Corr. 1, May be corrosive to metals.
- ⚠ Warning, Acute Tox. 4, Harmful if swallowed.
- ⚠ Warning, Acute Tox. 4, Harmful if inhaled.
- ⚠ Danger, Skin Corr. 1A, Causes severe skin burns and eye damage.
- ⚠ Danger, Eye Dam. 1, Causes serious eye damage.
- Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSTRIP A4512

Hazard pictograms:



Danger

Hazard statements:

H290 May be corrosive to metals.

H302+H332 Harmful if swallowed or if inhaled.

H314 Causes severe skin burns and eye damage.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P261 Avoid breathing vapours.

P264 Wash hands thoroughly after handling.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER if you feel unwell.

Special Provisions:

None

Contains

formic acid ... %

benzyl alcohol

BENZENESULPHONIC ACID,4-C10-13-SEC-ALKYL DERIVS

BENZYL FORMATE

benzothiazole-2-thiol: May produce an allergic reaction.

Special provisions according to Annex XVII of REACH and subsequent amendments:

Restricted to professional users.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
SOCOSTRIP A4512

Qty	Name	Ident. Number	Classification
>= 20% - < 25%	benzyl alcohol	Index number: CAS: 100-51-6 EC: 202-859-9 REACH No.: 01-2119492630-38	⚠ 3.1/4/Inhal Acute Tox. 4 H332 ⚠ 3.1/4/Oral Acute Tox. 4 H302 ⚠ 3.3/2 Eye Irrit. 2 H319 Acute Toxicity Estimate: ATE - Oral 1620 mg/kg bw
>= 7% - < 10%	BENZENESULPHONIC ACID,4-C10-13-SEC-ALKYL DERIVS	CAS: 85536-14-7 EC: 287-494-3 REACH No.: 01-2119490234-40	⚠ 3.1/4/Oral Acute Tox. 4 H302 ⚠ 3.3/1 Eye Dam. 1 H318 4.1/C3 Aquatic Chronic 3 H412 ⚠ 3.2/1B Skin Corr. 1B H314
>= 7% - < 10%	formic acid ... %	Index number: CAS: 64-18-6 EC: 200-579-1 REACH No.: 01-2119491174-37	⚠ 2.6/3 Flam. Liq. 3 H226 ⚠ 3.1/4/Oral Acute Tox. 4 H302 ⚠ 3.2/1A Skin Corr. 1A H314 ⚠ 3.1/3/Inhal Acute Tox. 3 H331 EUH071 Specific Concentration Limits: 2% <= C < 10%: Skin Irrit. 2 H315 2% <= C < 10%: Eye Irrit. 2 H319 10% <= C < 90%: Skin Corr. 1B H314 C >= 90%: Skin Corr. 1A H314
>= 3% - < 5%	BENZYL FORMATE	CAS: 104-57-4 EC: 203-214-4 REACH No.: Exempted----	⚠ 3.1/4/Dermal Acute Tox. 4 H312 ⚠ 3.1/4/Oral Acute Tox. 4 H302
>= 0.1% - < 0.25%	benzothiazole-2-thiol	Index number: CAS: 149-30-4 EC: 205-736-8 REACH No.: 01-2119485805-26	⚠ 3.4.2/1 Skin Sens. 1 H317 ⚠ 4.1/A1 Aquatic Acute 1 H400 ⚠ 4.1/C1 Aquatic Chronic 1 H410

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSTRIP A4512

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do NOT induce vomiting.

Give nothing to eat or drink.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

No particular treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO₂).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSTRIP A4512

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

benzyl alcohol - CAS: 100-51-6

- OEL Type: National - TWA(8h): 22 mg/m³, 5 ppm - Notes: Germany - DFG, H, Y,11

formic acid ... % - CAS: 64-18-6

- OEL Type: National - TWA(8h): 9 mg/m³, 5 ppm - Behaviour: Indicative - Notes: France
VLEP

- OEL Type: EU - TWA(8h): 9 mg/m³, 5 ppm

- OEL Type: ACGIH - TWA(8h): 5 ppm - STEL: 10 ppm - Notes: URT, eye, and skin irr

DNEL Exposure Limit Values

benzyl alcohol - CAS: 100-51-6

Worker Industry: 40 mg/kg b.w./day - Consumer: 20 mg/kg b.w./day - Exposure: Human
Dermal - Frequency: Short Term, systemic effects

Worker Industry: 110 mg/m³ - Consumer: 27 mg/kg b.w./day - Exposure: Human
Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 8 mg/kg b.w./day - Consumer: 4 mg/kg b.w./day - Exposure: Human
Dermal - Frequency: Long Term, systemic effects

Worker Industry: 22 mg/m³ - Consumer: 5.4 mg/m³ - Exposure: Human Inhalation -
Frequency: Long Term, systemic effects

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSTRIP A4512

Consumer: 20 mg/kg b.w./day - Exposure: Human Oral - Frequency: Short Term, systemic effects

BENZENESULPHONIC ACID,4-C10-13-SEC-ALKYL DERIVS - CAS: 85536-14-7

Worker Industry: 170 mg/kg b.w./day - Consumer: 85 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Long Term (repeated)

Worker Industry: 12 mg/m³ - Consumer: 3 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 12 mg/m³ - Consumer: 0.85 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term (repeated)

Consumer: 1.5 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 3 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects

Consumer: 42.5 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 0.425 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

formic acid ... % - CAS: 64-18-6

Worker Industry: 9.5 mg/m³ - Consumer: 3 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 19 mg/m³ - Consumer: 9.5 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 9.5 mg/m³ - Consumer: 3 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects

Worker Industry: 19 mg/m³ - Consumer: 9.5 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects

benzothiazole-2-thiol - CAS: 149-30-4

Consumer: 10 mg/kg b.w./day - Exposure: Human Oral - Frequency: Short Term, systemic effects

Consumer: 1.25 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Industry: 70.4 mg/m³ - Consumer: 17.6 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 8.8 mg/m³ - Consumer: 2.2 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 5 mg/kg b.w./day - Consumer: 2.5 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 40 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Short Term, systemic effects

Consumer: 1.25 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic effects

Consumer: 10 mg/kg b.w./day - Exposure: Human Oral - Frequency: Short Term, systemic effects

PNEC Exposure Limit Values

benzyl alcohol - CAS: 100-51-6

Target: Fresh Water - Value: 1 mg/l

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSTRIP A4512

Target: Marine water - Value: 0.1 mg/l

Target: PNEC01 - Value: 2.3 mg/l

Target: Soil - Value: 0.456 mg/kg

Target: Freshwater sediments - Value: 5.27 mg/kg

Target: Marine water sediments - Value: 0.527 mg/kg

Target: Microorganisms in sewage treatments - Value: 39 mg/l

BENZENESULPHONIC ACID,4-C10-13-SEC-ALKYL DERIVS - CAS: 85536-14-7

Target: Fresh Water - Value: 0.268 mg/l

Target: Water (intermittent discharge) - Value: 0.0167 mg/l

Target: Marine water - Value: 0.027 mg/l

Target: Marine water sediments - Value: 0.287 mg/kg dw

Target: Freshwater sediments - Value: 0.287 mg/kg dw

Target: Soil - Value: 35 mg/kg dw

Target: Sewage treatment plant - Value: 3.43 mg/l

formic acid ... % - CAS: 64-18-6

Target: Fresh Water - Value: 2 mg/l

Target: Marine water - Value: 0.2 mg/l

Target: Freshwater sediments - Value: 13.4 mg/kg

Target: Marine water sediments - Value: 1.34 mg/kg

Target: Soil (agricultural) - Value: 1.5 mg/kg

Target: Microorganisms in sewage treatments - Value: 7.2 mg/l

Target: Sporadic discharge - Value: 1 mg/l

benzothiazole-2-thiol - CAS: 149-30-4

Target: Sewage treatment plant - Value: 0.3 mg/l

Target: Freshwater sediments - Value: 0.147 mg/kg

Target: Marine water sediments - Value: 0.0147 mg/kg dw

Target: Marine water - Value: 0.00041 mg/l

Target: Fresh Water - Value: 0.0041 mg/l

Target: Soil - Value: 0.27 mg/kg dw

Biological Exposure Index

N.A.

8.2. Exposure controls

See below, example of PPE to use.

Eye protection:

Safety goggles (EN 166)

Face protection shield.

Use closed fitting safety goggles, don't use eye lens.

Protection for skin:

Complete head, face and neck protection.

Boots (NF EN13832-3)

Protection for hands:

Suitable gloves type: NF EN374

NBR (nitrile rubber).

NR (natural rubber, natural latex).

PVC (polyvinyl chloride)

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSTRIP A4512

Butyl rubber (isobutylene-isoprene copolymer)

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

Other conditions affecting workers exposure:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Physical state:	Liquid	--	--
Colour:	yellow / brown	--	--
Odour:	N.A.	--	--
Melting point/freezing point:	N.A.	--	--
Boiling point or initial boiling point and boiling range:	100 °C	--	--
Flammability:	N.A.	--	--
Lower and upper explosion limit:	Not Relevant	--	--
Flash point (°C):	130	--	--
Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	>260 °C	--	--
pH:	0.5	--	--
Kinematic viscosity:	N.A.	--	--
Solubility in water:	N.A.	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient n-octanol/water (log value):	N.A.	--	--
Vapour pressure:	N.A.	--	--

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSTRIP A4512

Density and/or relative density:	1.04	--	--
Relative vapour density:	N.A.	--	--
Particle characteristics:			
Particle size:	N.A.	--	--

9.2. Other information

No other relevant information

Volatile Organic compounds - VOCs = 21,1 %

Volatile Organic compounds - VOCs = 219 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological information of the product:

N.A.

Toxicological information of the main substances found in the product:

benzyl alcohol - CAS: 100-51-6

Acute toxicity:

Test: ATE - Route: Inhalation = 11 mg/l - Duration: 4h

ATE - Oral 1620 mg/kg bw

Test: LD50 - Route: Oral - Species: Rat (male) = 1620 mg/kg

ATE - Oral 1620 mg/kg bw

Test: ATE - Route: Oral = 1620 mg/kg

ATE - Oral 1620 mg/kg bw

Test: LD50 - Route: Oral - Species: Rat (Male, female) = 1620 mg/kg - Duration: 4h

ATE - Oral 1620 mg/kg bw

Carcinogenicity:

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSTRIP A4512

Route: Oral - Species: mouse (Male, female) = 400 mg/kg bw/day - Duration: 104 weeks -
Source: OECD 451

Reproductive toxicity:

Test: NOAEL - Route: Oral - Species: mouse (Male, female) = 200 mg/kg bw - Duration: 91 days

Test: NOAEL (fertility) - Route: Oral - Species: mouse (Male) = 800 mg/kg - Duration: 91 days

Test: NOAEL - Route: Oral - Species: Rat (Male, female) = 400 mg/kg bw - Duration: 91 days

Test: NOAEL (fertility) - Route: Oral - Species: Rat (Male, female) = 800 mg/kg bw - Duration: 91 days

Test: NOAEC - Route: Inhalation - Species: Rat (Male, female) = 1072 mg/m³ - Duration: 28 days - Source: OECD 412

Test: NOAEL (fertility) - Route: Inhalation - Species: Rat (Male, female) = 1072 mg/m³ - Duration: 28 days - Source: OECD 412

STOT-repeated exposure:

Test: NOAEC - Route: Inhalation (aerosol) - Species: Rat (Male, female) = 1072 mg/m³ - Duration: 28 days - Source: OECD 412

Test: NOAEL - Route: Oral - Species: Rat (Male, female) = 400 mg/kg - Duration: 103 weeks, 5 days/week - Source: OECD 451

Test: NOAEC - Route: Inhalation (dust, mist) - Species: Rat (Male, female) = 1072 mg/m³ - Duration: 28 days - Source: OECD 412

BENZENESULPHONIC ACID,4-C10-13-SEC-ALKYL DERIVS - CAS: 85536-14-7

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 1470 mg/kg

Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg

STOT-repeated exposure:

Test: NOAEL - Route: Oral - Species: Rat = 125 mg/kg - Duration: 28 days - Notes: gavage oral

Test: NOAEL - Route: Oral - Species: Rat = 40 mg/kg - Notes: 6 mois, alimentation orale

Test: NOAEL - Route: Oral - Species: Rat = 85 mg/kg - Notes: 9 mois, eau administrée oralement

formic acid ... % - CAS: 64-18-6

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 730 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 7.4 mg/l - Duration: 4h

Test: LD50 - Route: Skin - Species: Rat = 940 mg/kg

benzothiazole-2-thiol - CAS: 149-30-4

Acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 1270 mg/l - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat = 3800 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 7940 mg/kg

Carcinogenicity:

Test: LOAEL

- Route: Oral - Species: Rat = 375 mg/kg bw - Duration: 103 weeks, 5 days/week - Source:

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSTRIP A4512

OECD 451 - Notes: Male

Test: LOAEC - Route: Oral - Species: Rat = 188 mg/kg bw - Duration: 103 weeks, 5 days/week - Source: OECD 451 - Notes: Female

STOT-repeated exposure:

Test: LOAEL

- Route: Oral - Species: Rat = 2500 ppm - Duration: 70 days - Source: OECD 416 - Notes: Subchronic toxicity

benzyl alcohol - CAS: 100-51-6

LD50 (RABBIT) SKIN SINGLE DOSE: 2000 MG/KG

If not differently specified, the information required in Regulation (EU)2020/878 listed below must be considered as N.A.:

Acute toxicity;
Skin corrosion/irritation;
Serious eye damage/irritation;
Respiratory or skin sensitisation;
Germ cell mutagenicity;
Carcinogenicity;
Reproductive toxicity;
STOT-single exposure;
STOT-repeated exposure;
Aspiration hazard.

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration $\geq 0.1\%$

Other toxicological information:

benzyl alcohol

Skin corrosion / irritation:

Severe eye irritation.

Skin irritation:

Slight irritating effect

Mutagenicity on germ cells (in vitro):

Positive without metabolic activation, OECD 476, Mouse (L5178Y lymphoma cell)

Positive with metabolic activation, Chinese Hamster Ovary (CHO)

-

BENZENESULPHONIC ACID,4-C10-13-SEC-ALKYL DERIVS

Eye contact:

Severe eye damage

-

benzothiazole-2-thiol

Eye irritation:

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSTRIP A4512

Slight irritating effect
Skin sensitization:
May cause skin sensitization.

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

benzyl alcohol - CAS: 100-51-6

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 460 mg/l - Duration h: 96 - Notes: Pimephales promelas/ EPA OPP 72-1

Endpoint: EC50 - Species: Daphnia = 230 mg/l - Duration h: 48 - Notes: Daphnia magna, OECD 202

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 51 mg/l - Duration h: 504 - Notes: Daphnia magna, OECD 211

d) Terrestrial toxicity:

Endpoint: IC50 - Species: Microorganisms = 390 mg/kg - Duration h: 24 - Notes: ISO 8192; Nitrosomas

e) Plant toxicity:

Endpoint: NOEC - Species: Algae = 310 mg/l - Duration h: 72 - Notes: Pseudokirchneriella subcapitata, OECD 201

Endpoint: EC50 - Species: Algae = 770 mg/l - Duration h: 72 - Notes: Pseudokirchneriella subcapitata, OECD 201

BENZENESULPHONIC ACID,4-C10-13-SEC-ALKYL DERIVS - CAS: 85536-14-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 1.67 mg/l - Duration h: 96 - Notes: Lepomis Macrochirus

Endpoint: EC50 - Species: Daphnia = 2.9 mg/l - Duration h: 48 - Notes: Daphnia Magna

Endpoint: EC50 - Species: Algae = 47.3 mg/l - Duration h: 72 - Notes: Scenedesmus subspicatus

Endpoint: NOEC - Species: Algae = 2.4 mg/l - Duration h: 72 - Notes: Scenedesmus subspicatus

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish = 0.63 mg/l - Notes: 196J, Pimephales Promelas, LOEC : 1.2 mg/L

Endpoint: NOEC - Species: Daphnia = 1.41 mg/l - Notes: 21J

Endpoint: NOEC - Species: Algae = 3.1 mg/l - Notes: 15J, Chlorella Kessleri, LOEC : 10 mg/L

Endpoint: NOEC - Species: Algae > 4 mg/l - Notes: 28J, Elodea Canadensis

formic acid ... % - CAS: 64-18-6

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 46 mg/l - Duration h: 96 - Notes: Leuciscus idus

Endpoint: EC50 - Species: Daphnia = 32.19 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 26.9 mg/l - Duration h: 72 - Notes: Scenedesmus subspicatus

Endpoint: NOEC - Species: Daphnia > 102 mg/l - Duration h: 504

c) Bacteria toxicity:

Endpoint: EC10 - Species: bacteria = 72 mg/l - Duration h: 312 - Notes: Boue activée/activated sludge

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSTRIP A4512

Endpoint: EC50 - Species: bacteria = 46.7 mg/l - Duration h: 17

f) Effects in sewage plants (activated sludge):

Endpoint: EC20 - Species: Microorganisms > 1000 mg/l - Duration h: 0.5

benzothiazole-2-thiol - CAS: 149-30-4

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 0.71 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 0.25 mg/l - Duration h: 72

Endpoint: LC50 - Species: Fish = 0.73 mg/l - Duration h: 96

Endpoint: LC50 - Species: Daphnia = 4.1 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 0.08 mg/l - Duration h: 504

Endpoint: NOEC - Species: Algae = 0.066 mg/l - Duration h: 72

Endpoint: NOEC - Species: Fish 0.041 mg/l - Duration h: 2136

12.2. Persistence and degradability

benzyl alcohol - CAS: 100-51-6

Biodegradability: Biodegradation in water - Test: OECD 301C - Duration: 14 days - %: 92-96 -

Notes: OECD 301C

BENZENESULPHONIC ACID,4-C10-13-SEC-ALKYL DERIVS - CAS: 85536-14-7

Biodegradability: Biodegradable - Duration: 28 days - %: 96

formic acid ... % - CAS: 64-18-6

Biodegradability: Readily biodegradable

benzothiazole-2-thiol - CAS: 149-30-4

Biodegradability: Biodegradability rate - Test: OECD 301C - Duration: 14 days - %: 2.5

12.3. Bioaccumulative potential

benzyl alcohol - CAS: 100-51-6

BCF 1.37 l/kg

Log Kow 1.05 - Notes: 20°C

benzothiazole-2-thiol - CAS: 149-30-4

Log Pow 2.42

BCF - Test: OECD 305C < 8 - Duration: 14 days - Notes: Cyprinus carpio (25°C)

12.4. Mobility in soil

benzyl alcohol - CAS: 100-51-6

Log Koc 15.7

Volality (H: Henry's Law Constant) 0.0879 Pa.m³/mol

benzothiazole-2-thiol - CAS: 149-30-4

Log Koc 2.51 - 3.55

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration \geq 0.1%

12.7. Other adverse effects

No harmful effects expected.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSTRIP A4512

so doing, comply with the local and national regulations currently in force.

Codes of wastes (Décision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste):

14 06 03* Other solvents and solvent mixtures

SECTION 14: Transport information



14.1. UN number or ID number

ADR-UN Number: 3265
IATA-UN Number: 3265
IMDG-UN Number: 3265

14.2. UN proper shipping name

ADR-Shipping Name: CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.
(BENZENESULPHONIC ACID,4-C10-13-SEC-ALKYL DERIVS,
formic acid ...%)
IMDG-Shipping Name: CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.
(BENZENESULPHONIC ACID,4-C10-13-SEC-ALKYL DERIVS,
formic acid ...%)

14.3. Transport hazard class(es)

ADR-Class: 8
ADR - Hazard identification number: 80
IATA-Class: 8
IATA-Label: 8
IMDG-Class: 8

14.4. Packing group

ADR-Packing Group: II
IATA-Packing group: II
IMDG-Packing group: II

14.5. Environmental hazards

ADR-Environmental Pollutant: No
IMDG-Marine pollutant: No
IMDG-EmS: F-A , S-B

14.6. Special precautions for user

ADR-Subsidiary hazards: -
ADR-S.P.: 274
ADR-Transport category (Tunnel restriction code): 2 (E)
IATA-Passenger Aircraft: 851
IATA-Subsidiary hazards: -
IATA-Cargo Aircraft: 855
IATA-S.P.: A3 A803
IATA-ERG: 8L
IMDG-Subsidiary hazards: -
IMDG-Stowage and handling: Category B
IMDG-Segregation: Clear of living quarters.

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSTRIP A4512

Q.L.: 1L

Q.E.: E2

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restrictions related to the substances contained:

Restriction 28

Restriction 40

Restriction 75

Listed or in compliance with the following international inventories:

Labelling of detergents (EC Regulations 648/2004 and 907/2006):

N.A.

Labelling of biocides (Regulations 1896/2000, 1687/2002, 2032/2003, 1048/2005, 1849/2006, 1451/2007 and Directive 98/8/EC):

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSTRIP A4512

N.A.

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

1999/13/EC (VOC directive)

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

None

15.2. Chemical safety assessment

No

SECTION 16: Other information

N.A.: Not Applicable or Not Available

Full text of phrases referred to in Section 3:

H332 Harmful if inhaled.

H302 Harmful if swallowed.

H319 Causes serious eye irritation.

H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

H314 Causes severe skin burns and eye damage.

H226 Flammable liquid and vapour.

H331 Toxic if inhaled.

EUH071 Corrosive to the respiratory tract.

H315 Causes skin irritation.

H312 Harmful in contact with skin.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Hazard class and hazard category	Code	Description
Met. Corr. 1	2.16/1	Substance or mixture corrosive to metals, Category 1
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 3	3.1/3/Inhal	Acute toxicity (inhalation), Category 3
Acute Tox. 4	3.1/4/Dermal	Acute toxicity (dermal), Category 4

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSTRIP A4512

Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Skin Corr. 1A	3.2/1A	Skin corrosion, Category 1A
Skin Corr. 1B	3.2/1B	Skin corrosion, Category 1B
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Skin Sens. 1	3.4.2/1	Skin Sensitisation, Category 1
Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1
Aquatic Chronic 1	4.1/C1	Chronic (long term) aquatic hazard, category 1
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3

This safety data sheet has been completely updated in compliance to Regulation 2020/878. Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Met. Corr. 1, H290	On basis of test data
Acute Tox. 4, H302	Calculation method
Acute Tox. 4, H332	Calculation method
Skin Corr. 1A, H314	Calculation method
Eye Dam. 1, H318	Calculation method
Aquatic Chronic 3, H412	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van
Nostrand Reinold
CCNL - Appendix 1

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSTRIP A4512

Insert further consulted bibliography

Important confidentiality : this document contains confidential information that is proprietary to SOCOMORE. Subject to legal provisions determining otherwise, the distribution, republication or re-transmission of this document, in full or in part, must be limited to clearly identified individuals, either because they use the product, or to provide HSE information. Any communication of this document outside of this framework without our written consent is strictly forbidden.

SOCOMORE strongly advises every recipient of this safety data sheet to read it carefully and to consult experts in the field if necessary or appropriate, in order to understand the information it contains, notably the possible dangers associated with this product. The users must ensure the conformity and completeness of this information with regards to their specific use of the product.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the responsibility of the purchaser/user to ensure that their activities conform with current legislation in force.

The information is considered correct, but it is not exhaustive and it shall be used only as a guide which is based on the current knowledge of the substance or mixture and it is applicable to the safety precautions appropriate for the product.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSTRIP A4512

STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
STOT SE:	May cause drowsiness or dizziness
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.